

A 145 ... AF 750 3-pole Contactors - a.c. Coil

Ordering Details



A 145-30-11



A 300-30-11



AF 460-30-11



AF 750-30-11

Rated operational current	Auxiliary contacts fitted	Type	Order code		Weight kg
AC-3 380 V 400 V 415 V A	AC-1 $\theta \leq 40^\circ\text{C}$ A	State coil voltage: [][]	coil voltage code see table below : [][]		Pack ^{ing} 1 piece
145	250	1 1 2 2	A 145-30-11 [][] A 145-30-22 [][]	1SFL 47 1001 R [][]11 1SFL 47 1001 R [][]22	3.500 3.500
185	275	1 1 2 2	A 185-30-11 [][] A 185-30-22 [][]	1SFL 49 1001 R [][]11 1SFL 49 1001 R [][]22	3.500 3.500
210	350	1 1 2 2	A 210-30-11 [][] A 210-30-22 [][]	1SFL 51 1001 R [][]11 1SFL 51 1001 R [][]22	6.100 6.100
260	400	1 1 2 2	A 260-30-11 [][] A 260-30-22 [][]	1SFL 53 1001 R [][]11 1SFL 53 1001 R [][]22	6.100 6.100
305	500	1 1 2 2	A 300-30-11 [][] A 300-30-22 [][]	1SFL 55 1001 R [][]11 1SFL 55 1001 R [][]22	6.100 6.100
400	600	1 1 2 2	AF 400-30-11 [][] AF 400-30-22 [][]	1SFL 57 7001 R [][]11 1SFL 57 7001 R [][]22	12.000 12.000
460	700	1 1 2 2	AF 460-30-11 [][] AF 460-30-22 [][]	1SFL 59 7001 R [][]11 1SFL 59 7001 R [][]22	12.000 12.000
580	800	1 1 2 2	AF 580-30-11 [][] AF 580-30-22 [][]	1SFL 61 7001 R [][]11 1SFL 61 7001 R [][]22	15.000 15.000
750	1050	1 1 2 2	AF 750-30-11 [][] AF 750-30-22 [][]	1SFL 63 7001 R [][]11 1SFL 63 7001 R [][]22	15.000 15.000

Coil voltages and codes: A 145 ... A 300

Voltage (V) 50 Hz : [][]	Voltage (V) 60 Hz : [][]	Voltage code : [][]
24	24	[8] [1]
48	48	[8] [3]
110	110...120	[8] [4]
220 ... 230	230...240	[8] [0]
230 ... 240	240...260	[8] [8]
380 ... 400	400...415	[8] [5]
400 ... 415	415...440	[8] [6]

Other voltages : page 36.

Coil voltages and codes: AF 400 ... AF 750

Voltage (V) 50...60 Hz : [][]	Voltage (V) d.c. [][]	Voltage code : [][]
-	24...60	[6] [8]
48...130	48...130	[6] [9]
100...250	100...250	[7] [0]

>> Accessories page 10
>> Thermal and electronic O/L relays page 15

>> Technical data page 33
>> Dimensions page 51