DS201 M C10 A30



Products ₃ Low Voltage Products and Systems ₃ Modular DIN Rail Products ₃ Residual Current Devices RCDs ₃ Residual Current Circuit Breakers with Overcurrent Protection RCBO

General Information	
Extended Product Type:	DS201 M C10 A30
Product ID:	2CSR275140R1104
EAN:	8012542110354
Catalog Description:	DS201 M C10 A30 - RCBO
Long Description:	The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user si ngle-phase circuits against overload and short-circuit currents; protection against the effec ts of sinusoidal alternating and direct pulsating earth fault currents; protection against indir ect contacts and additional protection against direct contacts (with sensitivity = 30 mA).
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363010
Popular Downloads	
Data Sheet, Technical Information:	2CSC400002D0209
Dimensions	
Product Net Width:	0.035 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.239 kg
Technical	
Standards:	IEC 61009-1 IEC 61009-2-1
	EN 61009-1 EN 61009-2-1
Type of Residual Current:	
Type of Residual Current: Rated Residual Current:	EN 61009-2-1
	EN 61009-2-1 A type
Rated Residual Current:	EN 61009-2-1 A type 30 mA
Rated Residual Current: Tripping Characteristic:	EN 61009-2-1 A type 30 mA C
Rated Residual Current: Tripping Characteristic: Rated Current (I _n):	EN 61009-2-1 A type 30 mA C 10 A
Rated Residual Current: Tripping Characteristic: Rated Current (I _n): Number of Poles:	EN 61009-2-1 A type 30 mA C 10 A 2
Rated Residual Current: Tripping Characteristic: Rated Current (I _n): Number of Poles: Number of Protected Poles:	EN 61009-2-1 A type 30 mA C 10 A 2 1
Rated Residual Current: Tripping Characteristic: Rated Current (I _n): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (I _{cn}):	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA
Rated Residual Current: Tripping Characteristic: Rated Current (I _n): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (I _{cn}): Position of Neutral Terminals:	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right
Rated Residual Current: Tripping Characteristic: Rated Current (In): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (Icn): Position of Neutral Terminals: Power Loss:	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W
Rated Residual Current: Tripping Characteristic: Rated Current (In): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (Icn): Position of Neutral Terminals: Power Loss: Rated Voltage (Ur):	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W
Rated Residual Current:Tripping Characteristic:Rated Current (ln):Number of Poles:Number of Protected Poles:Rated Short-Circuit Capacity (lcn):Position of Neutral Terminals:Power Loss:Rated Voltage (Ur):Environmental	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W 230-240 V AC Operation -25 +55 °C
Rated Residual Current: Tripping Characteristic: Rated Current (ln): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (lcn): Position of Neutral Terminals: Power Loss: Rated Voltage (Ur): Environmental Ambient Air Temperature:	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W 230-240 V AC Operation -25 +55 °C Storage -40 +70 °C Following EU Directive 2011/65/EU
Rated Residual Current: Tripping Characteristic: Rated Current (ln): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (lcn): Position of Neutral Terminals: Power Loss: Rated Voltage (Ur): Environmental Ambient Air Temperature: RoHS Status:	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W 230-240 V AC Operation -25 +55 °C Storage -40 +70 °C Following EU Directive 2011/65/EU
Rated Residual Current: Tripping Characteristic: Rated Current (ln): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (lcn): Position of Neutral Terminals: Power Loss: Rated Voltage (Ur): Environmental Ambient Air Temperature: RoHS Status: Certificates and Declarations (Docu	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W 230-240 V AC Operation -25 +55 °C Storage -40 +70 °C Following EU Directive 2011/65/EU
Rated Residual Current: Tripping Characteristic: Rated Current (In): Number of Poles: Number of Protected Poles: Rated Short-Circuit Capacity (Icn): Position of Neutral Terminals: Power Loss: Rated Voltage (Ur): Environmental Ambient Air Temperature: RoHS Status: Certificates and Declarations (Docu Declaration of Conformity - CE	EN 61009-2-1 A type 30 mA C 10 A 2 1 (230 / 400 V AC) 10 kA Right 2.3 W 230-240 V AC Operation -25 +55 °C Storage -40 +70 °C Following EU Directive 2011/65/EU Iment Number) 9AKK106713A5588

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	0.253 m
Package Level 1 Height:	0.088 m
Package Level 1 Length:	0.108 m
Package Level 1 Gross Weight:	1.446 kg
Package Level 1 EAN:	8012542110361

Classifications

Object Classification Code:	Q
E-nummer:	2160240
ETIM 4:	EC000905 - Earth leakage circuit breaker
ETIM 5:	EC000905 - Earth leakage circuit breaker
ETIM 6:	EC000905 - Earth leakage circuit breaker

