F202 PV B-63/0,03



General Information

Extended Product Type: F202 PV B-63/0,03 Product ID: 2CSF202601R1630 EAN: 8012542368632

Catalog Description: F202 PV B-63/0,03 - Resid. Current Dev.

Long Description:

The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is particularly suitable for the protection against smooth DC earth fault current for photovoltaic applications.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Devices RCDs

Ordering

EAN: 8012542368632 Minimum Order Quantity: 1 piece **Customs Tariff Number:** 85363030

Dimensions

Product Net Width: 0.072 m **Product Net Height:** 0.085 m **Product Net Depth:** 0.069 m **Product Net Weight:** 0.500 kg

Container Information

Package Level 1 Units: 1 piece Package Level 1 Width: 0.073 m Package Level 1 Height: 0.078 m Package Level 1 Length: 0.09 m Package Level 1 Gross Weight: 0.525 kg Package Level 1 EAN: 8012542368632

Technical

Standards: IEC EN 61008 IEC 62423 Operating Characteristic: Instantaneous Type of Residual Current: B type - photovoltaic application **Rated Residual Current:** 30 mA Rated Current (In): 63 A

Number of Poles: 2

Power Loss: Per Pole 3.2 W

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: ITSCE168F202PVB **RoHS Information:** 2CSC423005K0201

Classifications

Object Classification Code:

ETIM 4.0: EC000003 - Residual current circuit breaker (RCCB) ETIM 5.0: EC000003 - Residual current circuit breaker (RCCB)

