

F204 A S-63/0,1



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs
Residual Current Devices RCDs

General Information

| | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type: | F204 A S-63/0,1 |
| Product ID: | 2CSF204201R2630 |
| EAN: | 8012542823407 |
| Catalog Description: | F204 A S-63/0,1 Residual Current Dev. |
| Long Description: | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

Additional Information

| | |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Country of Origin: | Italy (IT) |
| Customs Tariff Number: | 85363030 |
| Data Sheet, Technical Information: | 2CSC400002D0209 |
| Declaration of Conformity - CE: | 2CSC423001D2701 |
| EAN: | 8012542823407 |
| EPLAN Catalog Tree: | Electrical engineering / Protection devices / Ground fault current circuit breaker |
| EPLAN Function Definition: | Ground fault current circuit-breaker / Ground fault current circuit breakers, 8 connection points / Ground fault current circuit breaker, four-pole 1_2_3_4_5_6_N_N. |
| ETIM 4: | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 5: | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 6: | EC000003 - Residual current circuit breaker (RCCB) |
| Environmental Information: | S-P-00081 |
| Instructions and Manuals: | 2CSF423001D6402 |
| Invoice Description: | F204 A S-63/0,1 Residual Current Dev. |
| Maximum Operating Voltage UL/CSA: | 480Y / 277 V AC |
| Minimum Order Quantity: | 1 piece |
| Number of Poles: | 4 |
| Object Classification Code: | Q |
| Operating Characteristic: | Selective |
| Options Provided: | - |
| Package Level 1 EAN: | 8012542823407 |
| Package Level 1 Gross Weight: | 0.403 kg |
| Package Level 1 Height: | 0.078 m |
| Package Level 1 Length: | 0.096 m |
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 0.082 m |
| Position of Neutral Terminals: | Right |
| Power Loss: | at Rated Operating Conditions per Pole 4.4 W |
| Product Main Type: | F200 |
| Product Name: | Residual Current Device |
| Product Net Depth: | 0.069 m |
| Product Net Height: | 0.085 m |
| Product Net Weight: | 0.360 kg |
| Product Net Width: | 0.070 m |
| Rated Current (I_n): | 63 A |
| Rated Frequency (f): | 50 ... 60 Hz |
| Rated Operational Voltage: | 230 / 400 V AC |
| Rated Residual Current: | 100 mA |
| Rated Voltage (U_r): | 230/400 V |
| RoHS Information: | 2CSC423001K0201 |
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3 |
| Selling Unit of Measure: | piece |
| Short Description: | Residual Current Device F204 A S-63/0,1 |
| Standards: | IEC/EN 61008 UL 1053 |
| Type of Residual Current: | A type |
| Accessories Available: | Yes |

