

HK-11

ABB contact for United
Kingdom



General Information

Extended Product Type:	HK-11
Product ID:	1SAM101901R0001
EAN:	4013614139857
Catalog Description:	HK-11 Auxiliary Contact
Long Description:	HK-11 Aux.-contact 1NO+1NC

Categories

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

Ordering

EAN:	4013614139857
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Container Information

Package Level 1 Width:	210.0 mm
Package Level 1 Length:	79.0 mm
Package Level 1 Height:	105.0 mm
Package Level 1 Gross Weight:	0.365 kg
Package Level 1 EAN:	4013614442315
Package Level 1 Units:	10 piece

Dimensions

Product Net Width:	9.0 mm
Product Net Height:	86.0 mm
Product Net Depth:	72.0 mm
Product Net Weight:	0.030 kg

Technical

Rated Operational Voltage (U_e):	400 V AC 250 V DC
Rated Operational Current AC-15 (I_e):	(24V) 3 A (120V) 3 A (240V) 2 A (380 / 400V) 0.5 A
Rated Operational Current DC-13 (I_e):	(24V) 2.5 A (125V) 0.55 A (250V) 0,27 A
Rated Frequency (f_r):	Auxiliary Circuit DC Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U_i):	690 V
Degree of Protection:	IP20
Connecting Capacity-Auxiliary Circuit:	Rigid 1/2x 1.0 ... 2.5 mm ² Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ²

	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ²
	Flexible with Insulated Ferrule 2x 0.75 mm ²
Tightening Torques:	Auxiliary Circuit 0.8 ... 1.0 N·m
Wire Stripping Length:	Auxiliary Circuit 8 mm
Recommended Screw Driver:	Pozidriv 1
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Product Name:	Auxiliary Contact
Suitable For:	MS325 MO325
Suitable for Product Class:	Manual Motor Starters

Environmental

Ambient Air Temperature:	Operation -25 +50 °C Storage -50 ...+80 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Connecting Capacity-Auxiliary Circuit	Stranded 1/2x 14 ... 18 AWG
UL/CSA:	Flexible 1/2x 14 ... 8 AWG
Tightening Torques UL/CSA:	Auxiliary Circuit 7 in-lb
Contact Rating UL/CSA:	B300 Q300

Certificates and Declarations (Document Number)

CCC Certificate:	1SAA918001-3801
CSA Certificate:	1SAA918000-1102
cUL Certificate:	1SAA918002-1701
Declaration of Conformity - CE:	1SAD938510-0003
GOST Certificate:	1SAA918000-2703
UL Certificate:	1SAA918002-1601

Classifications

E-nummer:	3111370
Object Classification Code:	Q
UNSPSC:	39121500



