

General Information

Extended Product Type:	HKF1-11
Product ID:	1SAM201901R1001
EAN:	4013614320354
Catalog Description:	HKF1-11 Auxiliary Contact
Long Description:	HKF1-11 Aux.-contact for frontmounting

Categories

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

Ordering

EAN:	4013614320354
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	45.0 mm
Product Net Depth:	26.5 mm
Product Net Height:	12.5 mm
Product Net Weight:	0.015 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	148.0 mm
Package Level 1 Length:	36.0 mm
Package Level 1 Height:	50.0 mm
Package Level 1 Gross Weight:	0.195 kg
Package Level 1 EAN:	4013614481413

Environmental

Ambient Air Temperature:	Operation -20 ... +55 °C Storage -20 ... +70 °C Storage -50 ... +80 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Rated Operational Voltage:	250 V
Rated Insulation Voltage (U _i):	250 V
Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.2 N·m
Recommended Screw Driver:	Pozidriv 2 M3
Mounting Position:	Position 1 to 6

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 250 V
Connecting Capacity-Auxiliary Circuit UL/CSA:	Stranded 1/2x 16 ... 14 AWG Flexible 1/2x 16 ... 14 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in-lb

Certificates and Declarations (Document Number)

ABS Certificate:	1SAA963001-0101
BV Certificate:	1SAA963000-0202
CB Certificate:	1SAA963003-2001
CCC Certificate:	1SAA963002-3802
cUL Certificate:	cUL_E137861
Declaration of Conformity - CE:	1SAD938501-0188 1SAD938508-0125

	1SAD938503-0183
	1SAD938515-0060
DNV Certificate:	1SAA963001-0303
GL Certificate:	1SAA963001-0401 1SAA963000-0402
GOST Certificate:	1SAA937000-2703
LR Certificate:	1SAA963000-0504 1SAA963001-0501
RINA Certificate:	1SAA963000-0801
RoHS Information:	1SAA963001-4407
UL Certificate:	UL_E137861

Classifications

E-nummer:	3112001
ETIM 4.0:	EC002498 - Accessories for low-voltage switch technology
ETIM 5.0:	EC002498 - Accessories for low-voltage switch technology
Object Classification Code:	Q
UNSPSC:	39121500

