

General Information

Extended Product Type:	UA1-24
Product ID:	1SAM201904R1001
EAN:	4013614320422
Catalog Description:	UA1-24 Undervoltage Release
Long Description:	UA1-24 Undervoltage release 24 V

Additional Information

ABS Certificate:	1SAA963001-0101
Ambient Air Temperature:	Operation -25 +60 °C Storage -50 ...+80 °C
BV Certificate:	1SAA963000-0204
Connecting Capacity Auxiliary Circuit UL/CSA:	Stranded 1/2x 16 ... 12 AWG Flexible 1/2x 16 ... 12 AWG
Connecting Capacity Auxiliary Circuit:	Rigid 1/2x 1 ... 4 mm ² Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ²
Country of Origin:	Germany (DE)
Customs Tariff Number:	85365080
DNV Certificate:	1SAA963001-0303
Data Sheet, Technical Information:	1SBC100192C02--
Declaration of Conformity - CE:	1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938504-0183 1SAD938502-0190 1SAD938510-0125
E-number:	3112021
EAN:	4013614320422
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
ETIM 6:	EC002498 - Accessories for low-voltage switch technology
GL Certificate:	1SAA963001-0401 1SAA963000-0402
GOST Certificate:	1SAA937000-2703
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Invoice Description:	UA1-24 Undervoltage release 24 V
LR Certificate:	1SAA963001-0502 1SAA918001-0501
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 6
Package Level 1 Gross Weight:	0.11 kg
Package Level 1 Height:	80 mm

Package Level 1 Length:	25 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	93 mm
Package Level 2 EAN:	4013614526084
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Width:	280 mm
Product Main Type:	UA1
Product Name:	Undervoltage Release
Product Net Depth:	75.5 mm
Product Net Height:	90 mm
Product Net Weight:	0.1 kg
Product Net Width:	18 mm
RINA Certificate:	1SAA963000-0802
Rated Control Supply Voltage (U _s):	AuCircuit 24 V AC AuCircuit 50 Hz
Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i):	690 V
Recommended Screw Driver:	Pozidriv 2
RoHS Date:	0276
RoHS Information:	1SAA963001-4407
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	UA1-24 Undervoltage release 24V
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS116 MS132
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.2 N·m
UL Certificate:	UL_E137861
UNSPSC:	39120000
Wire Stripping Length:	Auxiliary Circuit 10 mm
cUL Certificate:	cUL_E137861
eClass:	7.0 27379201



