

General Information

Product ID:	1SDA067604R1
EAN:	8015644015008
Catalog Description:	XT2H 160 TMA 160-1600 3p F F
Long Description:	Automatic moulded case circuit-breakers, SACE Tmax XT XT2, Icu 415 V AC = 70kA, Size Iu = 160A , Thermomagnetic trip unit with adjustable thermal and magnetic threshold, In = 160A, Im = 1600A, 3 poles, Version = Fixed, connection terminal = Front terminal

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax XT

Ordering

EAN:	8015644015008
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	90 mm
Product Net Height:	130 mm
Product Net Depth:	82.5 mm
Product Net Weight:	1.1 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	130 mm
Package Level 1 Height:	208 mm
Package Level 1 Length:	145 mm
Package Level 1 Gross Weight:	1.2 kg
Package Level 1 EAN:	8015644015008

Additional Information

Electrical Durability:	120 cycles per hour 8000 cycle
Isolating Function:	Yes
Mechanical Durability ():	Nr. Operations 240 cycles per hour Nr. Operations 25000 cycle
Number of Poles:	3
Opening Time:	CB with SOR 15 ms CB with UVR 15 ms
Power Loss:	Per Pole 16.15 W
Product Main Type:	SACE Tmax XT
Product Name:	XT2
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220V AC) 100 kA (230V AC) 100 kA (380V AC) 70 kA (415V AC) 70 kA (440V AC) 65 kA (500V AC) 50 kA (690V AC) 15 kA (250V DC) 2 poles in series 70 kA (500V DC) 3 poles in series 70 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220V AC) 100 kA (230V AC) 100 kA (380V AC) 70 kA (415V AC) 70 kA (440V AC) 65 kA (500V AC) 50 kA (690V AC) 15 kA (250V DC) 2 poles in series 70 kA (500V DC) 3 poles in series 70 kA
Version:	Fixed

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: [1SDL000158R0151](#);

Classifications

Object Classification Code: Q

UNSPSC: 39120000

