



POINT Guard I/O Safety Module - 4 Safety Analog Input Module
(Compatible with terminal bases with 12 terminations)

- 24V DC I/O circuits
- 8 inputs or 8 outputs

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--------------------------------|---|
| Product Series | PointGuard I/O (Bul. 1734) |
| Component Type Fieldbus I/O | Safety Analogue Input Module |
| Number of Safe Analogue Inputs | 4 qty |
| Analogue Input Type(s) | Current / Voltage: Single-Ended |
| Analogue Input Range(s) | -5 ... 5V DC -10 +10V DC 0 ... 24V DC 0 ... 20mA |
| Analogue Resolution, Input | 12 bit (signed) |
| Power Supply | 24V DC |
| Operating Temperature, Max | 55 °C max |
| Operating Temperature, Min | -20 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -40 °C min |
| Relative Humidity, Max | 95 %RH |
| Humidity Type | Non-condensing |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |