

Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LDG2C			1492-LDG3				1492-LDG3C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	Single-circuit, two-level grounding terminal block with 2 connection points on each side			Two-circuit grounding terminal block with 1 feed-through and 1 ground circuit				Single-circuit, two-level grounding terminal block with 2 connection points on each side			
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	600V AC/DC		800V AC/DC	550V AC/DC	—	—	—	—
Maximum Current	Grounding			20 A	25 A	24 A	20 A	Grounding			
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#26...12 AWG	#30...12 AWG	2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...12 AWG	#30...12 AWG	2.5 mm ²	0.5...2.5 mm ² (20...14 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.				
Color: Green/Yellow	1492-LDG2C	50	—	—		1492-LDG3C	25				
Grey	—	—	1492-LDG3	25		—	—				
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.				
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10		199-DR1	10				
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10		1492-DR5	10				
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2	1492-DR6	2		1492-DR6	2				
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2		1492-DR7	2				
End Barrier Yellow	1492-EBLD2-Y	20	—	—		1492-EBLD3-Y	20				
Grey	—	—	1492-EBLD3	20		—	—				
End Anchors and Retainers											
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20		1492-ERL35	20				
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100		1492-EAJ35	100				
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50		1492-EAHJ35	50				
Other Accessories:											
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100	1492-PSLS2-2	100		1492-PSLS2-2	100				
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL2-5	100	1492-PSLS2-5	100		1492-PSLS2-5	100				
Test Plug (Stackable)	1492-TPL4	25	—	—		—	—				
Marking Systems:											
Snap-In Marker Cards	*	1492-M3X12 (120/card)	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5				
Snap-In Marker Cards		1492-M3X5 (100/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5				

* May only be mounted in terminal block corner marking positions.

