

Solid rubber international plugs and couplings

- Up to max. H07RN-F 3G 2.5 mm<sup>2</sup>
- Belgian/French system IP44, thermoplastic and solid rubber version, with snap latch

Art. no.	Version	Unit
<b>Solid rubber plug, 16A/250V~</b>		<b>earthing contact/UTE</b>
IP44		
913.169	<ul style="list-style-type: none"> <li>· With dual earthing contact</li> <li>· Screws to side, screw and surface terminals</li> <li>· Black</li> </ul>	20 items
<b>Solid rubber coupling, 16A/250V~</b>		<b>earthing contact/UTE</b>
IP44		
919.169	<ul style="list-style-type: none"> <li>· With snap latch and protection against contact</li> <li>· With thermoplastic cover</li> <li>· Black</li> </ul>	10 items



Non-heating appliance plugs and sockets 

Art. no.	Version	Unit
<b>Non-heating appliance plug with earthing contact</b>		
C14, 10A/250V~, 70°C		
<ul style="list-style-type: none"> <li>· For cables up to 3G 1.00 mm<sup>2</sup>, thermoplastic version with earthing contact C14 for cable mounting</li> <li>· Screw terminals, protective rubber sleeve and strain relief</li> </ul>		
915.171	· Black	50 items
915.271	· White	50 items
915.971	· Grey (RAL7035)	50 items
<b>Right angle non-heating appliance plug with earthing contact</b>		
C14, 10A/250V~, 70°C		
<ul style="list-style-type: none"> <li>· For cables up to 3G 1.00 mm<sup>2</sup>, thermoplastic version with earthing contact C14 for cable mounting</li> <li>· Screw terminals, protective rubber sleeve and strain relief, cable exit to right</li> </ul>		
915.172	· Black	50 items
<b>Non-heating appliance socket with earthing contact</b>		
C13, 10A/250V~, 70°C		
<ul style="list-style-type: none"> <li>· For cables up to 3G 1.00 mm<sup>2</sup>, thermoplastic version with earthing contact C13 for cable mounting</li> <li>· Screw terminals, protective rubber sleeve and strain relief</li> </ul>		
915.170	· Black	25 items
915.270	· White	25 items
915.970	· Grey (RAL7035)	25 items
<b>Non-heating appliance right angle socket with earthing contact</b>		
C13, 10A/250V~, 70°C		
<ul style="list-style-type: none"> <li>· For cables up to 3G 1.00 mm<sup>2</sup>, thermoplastic version with earthing contact C13 for cable mounting</li> <li>· Screw terminals, protective rubber sleeve and strain relief, cable exit to right</li> </ul>		
915.173	· Black	25 items
915.973	· Grey (RAL7035)	25 items
<b>Non-heating appliance built-in plug</b>		
C14, E, 10A/250V~, 70°C		
<ul style="list-style-type: none"> <li>· Thermoplastic version with screw terminal</li> </ul>		
917.170	· Black	50 items

