



## EP2338-100x | 8-channel digital input or output 24 V DC, 3 ms

The EP2338-100x EtherCAT Box has eight digital channels, each of which can optionally be operated as an input or as an output. A configuration for using a channel as input or output is not necessary; the input circuit is internally connected to the output driver, so that a set output is displayed automatically in the input process image.

The outputs handle load currents of up to 0.5 A, are short-circuit proof and protected against inverse polarity. The filter constant of the inputs is 3 ms.

The state of each signal is indicated by means of light emitting diodes. The signals are connected via M8 (EP2338-1001) or M12 connectors (EP2338-1002).

Technical data	EP2338-1001	EP2338-1002
<b>Specification</b>	EN 61131-2, type 1/3	
<b>Number of channels</b>	8 digital inputs or outputs	
<b>Input/output connections</b>	M8, screw type	M12, screw type
<b>Protocol</b>	EtherCAT	
<b>Bus interface</b>	2 x M8 socket, shielded, screw type	
<b>Input filter</b>	3.0 ms	
<b>"0" signal voltage</b>	-3...+5 V	
<b>"1" signal voltage</b>	11...30 V, 6 mA input current (EN 61131-2, type 3)	
<b>Sensor supply</b>	from load supply voltage, max. 0.5 A, short-circuit proof in total	
<b>Load type</b>	ohmic, inductive, lamp load	
<b>Rated load voltage</b>	24 V DC (-15 %/+20 %)	
<b>Max. output current</b>	0.5 A per channel, individually short-circuit proof	
<b>Short-circuit current</b>	typ. 1.5 A	
<b>Auxiliary power current</b>	typ. 20 mA + load	
<b>Current consumption from Us</b>	120 mA	
<b>Power supply connection</b>	feed: 1 x M8 male socket, 4-pin; downstream connection: 1 x M8 female socket, 4-pin	
<b>Bit width in the process image</b>	8 inputs + 8 outputs	
<b>Electrical isolation</b>	500 V	
<b>Weight</b>	approx. 165 g	
<b>Operating/storage temperature</b>	-25...+60 °C/-40...+85 °C	
<b>Vibration/shock resistance</b>	conforms to EN 60068-2-6/EN 60068-2-27	
<b>EMC immunity/emission</b>	conforms to EN 61000-6-2/EN 61000-6-4	
<b>Protect. class/installation pos.</b>	IP 65/66/67 (conforms to EN 60529)/variable	
<b>Approvals/Markings</b>	CE, UL, ATEX	
<b>Ex-Marking</b>	II 3 G Ex nA IIC T4 Gc	

Accessories	
ZK1090-3xxx-xxxx	Cables for EtherCAT signal in- and -output
ZK2000-xxxx-xxxx	Cables for M8 I/O connection sockets
ZK2000-6xxx-xxxx	Cables for M12 I/O connection sockets
ZK2020-3xxx-xxxx	Cables for M8 power supply