

C6015-0010 | Ultra compact industrial PC

Intel® Atom™ with up to four cores

Variants	Processor	available
C6015-0010	Intel® Atom™, 1 Core (TC3: 40*), Intel® Atom™, 2 Cores (TC3: 40*) or Intel® Atom™, 4 Cores (TC3: 50*)	yes

*The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see [here](#) for an overview of the TC3 performance classes.

C6015-0010	Fanless control cabinet PC
Housing	fanless industrial PC for space-saving control cabinet installation
	mounting plate on the rear wall
	all connectors on the same level
	flexible mounting mechanism for the free alignment of the connecting area
	aluminium zinc die-cast housing
	status LEDs
	lithium battery easily accessible
	1 slot for one M.2 SSD easily accessible
	passive, fanless cooling with one-sided cool plate
	5 cm (2") free space on top and bottom of the PC necessary for air circulation
	protection class IP 20
operating temperature 0...55 °C	
compact dimensions (W x H x D) 82 x 82 x 40 mm (3.2" x 3.2" x 1.6") without mounting plate	
Features	Intel® Atom™ E3815, 1.46 GHz, 1 core (TC3: 40)
	compact motherboard for Intel® Atom™
	2 GB DDR3L RAM, expandable ex factory to 4 GB
	Graphic adapter integrated inside the Intel® processor, 1 DisplayPort
	on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector
	30 GB M.2 SSD, 3D flash, extended temperature range
	1 USB 3.0 port and 1 USB 2.0 port
	24 V DC power supply
Microsoft Windows Embedded Compact 7, English	

Options	C6015-0010
C9900-C582	processor Intel® Atom™ E3827, 1.75 GHz, 2 cores (TC3: 40) and memory extension to 4 GB DDR3L RAM instead of Intel® Atom™ E3815, 1.46 GHz (TC3: 40) and 2 GB DDR3L RAM main memory. Memory extension requires a 64 bit operating system or only 3 GB are addressable. With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 IoT Enterprise.
C9900-C583	processor Intel® Atom™ E3845, 1.91 GHz, 4 cores (TC3: 50) and memory extension to 4 GB DDR3L RAM instead of Intel® Atom™ E3815, 1.46 GHz (TC3: 40) and 2 GB DDR3L RAM main memory. Memory extension requires a 64 bit operating system or only 3 GB are addressable. Operating temperature range 0...50 °C With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 IoT Enterprise.
C9900-H591	60 GB M.2 SSD, 3D flash, extended temperature range, instead of 30 GB M.2 SSD
C9900-Z468	adapter cable DisplayPort to DVI, 40 cm
C9900-M664	mounting plate for C6015 at the side wall, instead of plate at the rear wall
C9900-M665	mounting plate for lateral installation of the C6015; single part, not mounted
C9900-S706	TwinCAT 2 PLC runtime for Windows Embedded Compact 7
C9900-S707	TwinCAT 2 NC PTP runtime for Windows Embedded Compact 7
C9900-S708	TwinCAT 2 NC I runtime for Windows Embedded Compact 7