

# C6920-0050 | Control cabinet Industrial PC

Variants	Processor	available
<b>C6920-0020</b>	Intel® Core™2 Duo (TC3: 70*)	yes
<b>C6920-0030</b>	Intel® Celeron®, 2 Cores (TC3: 60*) or Intel® Core™2 Duo (TC3: 70*)	yes
<b>C6920-0040</b>	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*)	yes
<b>C6920-0050</b>	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*) (4th generation)	yes C9900-C570, C9900-C571 from May 2015

\*The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see [here](#) for an overview of the TC3 performance classes.

C6920-0050	Control cabinet PC
<b>Housing</b>	industrial PC for space-saving control cabinet installation
	mounting sheet at the rear wall
	all connectors on the front
	status LEDs
	lithium battery accessible behind the front flap
	1 slot for one 2½-inch hard disk or SSD behind the front flap
	1 slot for one CFast card behind the front flap
	fan cartridge with speed control and double ball bearing fans, accessible from the front
	5 cm (2") free space above and under the PC required for air circulation
	protection class IP 20
	operating temperature 0...55 °C
	weight of the basic configuration 1.9 kg (4.2 lbs)
<b>Features</b>	compact dimensions (W x H x D) 65 x 231 x 119 mm (2.6" x 9.1" x 4.7") without mounting plate
	processor Intel® Celeron® 2000E 2.2 GHz, 2 cores (TC3: 50)
	3½-inch motherboard for 4th Generation Intel® Core™ i3, Core™ i5, Core™ i7 or Celeron®
	1 Mini PCI slot free for cards installed ex factory
	2 GB DDR3L RAM, expandable to 16 GB
	graphic adapter integrated inside the Intel® processor, 1 DVI-I connector
	on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector
	on-board SATA RAID 1 controller, Intel® Rapid Storage Technology
	hard disk, 2½-inch, 320 GB
	1 serial port RS232, 2 USB 3.0 ports and 2 USB 2.0 ports
	24 V DC power supply

Options	C6920-0050
<b>C9900-C562</b>	processor 4th Generation Intel® Core™ i3 4100E, 2.4 GHz, 2 cores (TC3: 60), instead of Intel® Celeron® 2000E 2.2 GHz (TC3: 50)
<b>C9900-C570</b>	processor 4th Generation Intel® Core™ i3 4110E, 2.6 GHz, 2 cores (TC3: 60), instead of Intel® Celeron® 2000E 2.2 GHz (TC3: 50)
<b>C9900-C563</b>	processor 4th Generation Intel® Core™ i5 4400E, 2.7 GHz, 2 cores (TC3: 70), instead of Intel® Celeron® 2000E 2.2 GHz (TC3: 50)
<b>C9900-C571</b>	processor 4th Generation Intel® Core™ i5 4410E, 2.9 GHz, 2 cores (TC3: 70), instead of Intel® Celeron® 2000E 2.2 GHz (TC3: 50)
<b>C9900-C564</b>	processor 4th Generation Intel® Core™ i7 4700EQ, 2.4 GHz, 4 cores (TC3: 80), instead of Intel® Celeron® 2000E 2.2 GHz (TC3: 50)
<b>C9900-R257</b>	memory extension to 4 GB DDR3L RAM, instead of 2 GB, requires a 64 bit operating system or only 3 GB are addressable
<b>C9900-R258</b>	memory extension to 8 GB DDR3L RAM, instead of 2 GB, requires a 64 bit operating system
<b>C9900-R259</b>	memory extension to 16 GB DDR3L RAM, instead of 2 GB, requires a 64 bit operating system
<b>C9900-B506</b>	2 PCIe plug-in card slots on the passive backplane integrated inside C6920, to plug-in PCIe x1 cards up to 190 mm (7.5") length. The connectors of the plug-in cards are located at the top side of the PC on the right. The width of the PC housing is increased by 70 mm (2.76"), the depth is increased by 18 mm (0.7").

C9900-B510	2 PCI plug-in card slots on the passive backplane integrated inside C6920, to plug-in PCI cards up to 190 mm (7.5") length. The connectors of the plug-in cards are located at the top side of the PC on the right. The width of the PC housing is increased by 70 mm (2.76"), the depth is increased by 18 mm (0.7").
C9900-B514	1 PCI and 1 PCIe plug-in card slot on a passive backplane integrated inside C6920, to plug-in one PCI and one PCIe x1 card up to 190 mm (7.5") length. The connectors of the plug-in cards are located at the top side of the PC on the right. The width of the PC enclosure is increased by 70 mm (2.76"), the depth is increased by 18 mm (0.7").
C9900-E238	additional DVI-D plug led out on a slot bracket, only for PCs with plug-in card slots
C9900-M653	mounting plate at the side wall, instead of plate at the rear wall
C9900-E252	Serial port RS232, optically linked, overload protection, D-sub 9-pin connector. An additional fieldbus card or an additional serial interface is not possible.
C9900-E253	Serial port RS485, optically linked, overload protection, D-sub 9-pin connector. An additional fieldbus card or an additional serial interface is not possible. Configuration as an end point without echo: echo off, auto send on, always send off, auto receive on, always receive off, termination on
C9900-E254	Serial port RS422, optically linked, overload protection, D-sub 9-pin connector. An additional fieldbus card or an additional serial interface is not possible. Configuration as a full duplex end point: echo on, auto send off, always send on, auto receive off, always receive on, termination on
C9900-Z411	adapter plug DVI-I to VGA
C9900-Z413	adapter cable DVI-I to DVI and VGA 15 cm
C9900-R230	memory module NOVRAM for fail-safe storage of process data, 128 kB, Mini PCI plug-in card
C9900-R231	memory module NOVRAM for fail-safe storage of process data, 256 kB, Mini PCI plug-in card
C9900-R232	memory module NOVRAM for fail-safe storage of process data, 512 kB, Mini PCI plug-in card
C9900-D190	2 slots for CFast cards, instead of 1 slot for a 2½-inch hard disk or SSD and 1 slot for CFast
C9900-H701	solid-state disk SSD, SLC flash, 2½-inch, 32 GB, instead of 2½-inch hard disk
C9900-H706	solid-state disk SSD, SLC flash, 2½-inch, 64 GB, instead of 2½-inch hard disk
C9900-H736	solid-state disk SSD, SLC flash, 2½-inch, 128 GB, instead of 2½-inch hard disk
C9900-H550	4 GB CFast card, SLC flash, extended temperature range
C9900-H551	8 GB CFast card, SLC flash, extended temperature range
C9900-H552	16 GB CFast card, SLC flash, extended temperature range
C9900-H563	32 GB CFast card, SLC flash, extended temperature range
C9900-H553	4 GB CFast card, SLC flash, extended temperature range, instead of 2½-inch hard disk, less price
C9900-H554	8 GB CFast card, SLC flash, extended temperature range, instead of 2½-inch hard disk
C9900-H555	16 GB CFast card, SLC flash, extended temperature range, instead of 2½-inch hard disk
C9900-H565	32 GB CFast card, SLC flash, extended temperature range, instead of 2½-inch hard disk
C9900-U209	uninterruptible power supply UPS, integrated into the 24 V power supply, without battery, occupies one internal serial Interface
C9900-U330	battery pack for PCs with 24 V power supply and integrated UPS C9900-P209 or C9900-U209, external, for DIN rail mounting, 3.4 Ah, operating temperature 0...50 °C



C6920-0040 with plug-in card slots



Top view