



EK1501 | EtherCAT Coupler with ID switch, fibre optic

The EK1501 coupler connects EtherCAT with the EtherCAT Terminals (ELxxxx). A station consists of an EK1501 coupler, any number of EtherCAT Terminals, an EL9011 bus end cap or an EK1110 EtherCAT extension. The coupler converts the passing telegrams from Ethernet 100BASE-FX to E-bus signal representation. The multimode glass fibre connection enables distances of up to 2 km between two couplers – or up to 20 km for the EK1501-0010 with singlemode glass fibre connection.

The EK1501 has three hexadecimal ID switches for assigning an ID to a group of EtherCAT components. This group can then be located at any position within the EtherCAT network. Variable topologies are therefore easily implementable.

| Technical data | EK1501 | EK1501-0010 |
|-----------------------------------|---|--------------------------------------|
| Task within EtherCAT system | coupling of EtherCAT Terminals (ELxxxx) to 100BASE-FX EtherCAT networks, with identity verification | |
| Data transfer medium | multimode glass fibre 50/125 µm (MM) | singlemode glass fibre 9/125 µm (SM) |
| Distance between stations | max. 2,000 m (100BASE-FX) | max. 20,000 m (100BASE-FX) |
| Number of EtherCAT Terminals | up to 65,534 | |
| Type/number of peripheral signals | max. 4.2 GB addressable I/O points | |
| Number of configurable IDs | 4,096 | |
| Protocol | EtherCAT | |
| Delay | approx. 1 µs | |
| Data transfer rates | 100 Mbaud | |
| Configuration | not required | |
| Bus interface | 2 x SC Duplex | |
| Power supply | 24 V DC (-15 %/+20 %) | |
| Input current | 130 mA + (total E-bus current)/4 | 150 mA + (total E-bus current)/4 |
| Current consumption E-bus | – | |
| Current consumption 24 V DC | typ. 70 mA | |
| Current supply E-bus | 2000 mA | |
| Power contacts | 24 V DC max./10 A max. | |
| Weight | approx. 190 g | |
| Operating/storage temperature | -25...+60 °C/-40...+85 °C | |
| Relative humidity | 95 %, no condensation | |
| Vibration/shock resistance | conforms to EN 60068-2-6/EN 60068-2-27 | |
| EMC immunity/emission | conforms to EN 61000-6-2/EN 61000-6-4 | |
| Protect. class/installation pos. | IP 20/variable | |
| Approvals | CE, UL, Ex | |

| Accessories | |
|-------------|-------------------------|
| Cordsets | cordsets and connectors |

| | |
|-------------------------------------|--|
| Further fibre optic products | |
| EK1521 | 1-port EtherCAT multi-mode fibre optic junction |
| EP9521 EP9522 | EtherCAT/Industrial Ethernet modules EP952x for Industrial Fast Ethernet/100 Mbaud |