


Series: LER-PATH

Pressed steel castors with bolt hole fitting, wheel with thermoplastic polyurethane tread

150 - 300 kg

RoHS



Brackets: LER series - Made of pressed steel, with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free. Bracket overview: Page 65 Wheel and swivel head 'stop-fix' brake: Page 80

Wheels: PATH series - Tread: Made of high-quality thermoplastic polyurethane, 94° shore A, dark grey, non-marking, non-staining. Wheel centre: Made of high-quality, impact-resistant nylon, silver grey. Bearing types: Plain bore, roller bearing or a centrally encapsulated ball bearing (C). Ball bearing (C) for wheel Ø 80-125 mm with synthetic thread guard as standard. Detailed description: Page 208 and 42

8



Swivel castors	Swivel castors with 'stop-fix' brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LER-PATH 80G	LER-PATH 80G-FI	80	32	150	Plain bore	102	70	13	38
LER-PATH 80K-FK	LER-PATH 80K-FI-FK	80	32	150	Ball bearing (C)	102	70	13	38
LER-PATH 100G	LER-PATH 100G-FI	100	32	150	Plain bore	125	70	13	36
LER-PATH 100K-FK	LER-PATH 100K-FI-FK	100	32	150	Ball bearing (C)	125	70	13	36
LER-PATH 125G	LER-PATH 125G-FI	125	32	150	Plain bore	150	70	13	40
LER-PATH 125K-FK	LER-PATH 125K-FI-FK	125	32	150	Ball bearing (C)	150	70	13	40
LER-PATH 160G	LER-PATH 160G-FI	160	40	300	Plain bore	195	88	13	54
LER-PATH 160R	LER-PATH 160R-FI	160	40	300	Roller bearing	195	88	13	54
LER-PATH 160K	LER-PATH 160K-FI	160	40	300	Ball bearing (C)	195	88	13	54
LER-PATH 200G	LER-PATH 200G-FI	200	40	300	Plain bore	235	88	13	54
LER-PATH 200R	LER-PATH 200R-FI	200	40	300	Roller bearing	235	88	13	54
LER-PATH 200K	LER-PATH 200K-FI	200	40	300	Ball bearing (C)	235	88	13	54

For stainless steel versions refer to page 363

Options



	Image plain bore version	Electrically conductive version, non-marking grey *	With synthetic foot guard	With stainless steel axle tube in the wheel hub	With stainless steel roller bearing in the wheel hub	Wheel with additional ball bearing seals
Technical description page		36, 39	84	85	60	61
Product code suffix		-ELS	-FP	-XA	-XR	-KD
Available for		all ball bearing versions	wheel Ø 125 mm upon request	plain bore versions upon request	upon request	upon request

* Load capacity is reduced by 35 %