

Modular fuse holders

10 x 38 mm, CH

Specifications

Description

Compact DIN-Rail mounting fuse holders for 10 x 38 mm cylindrical fuse links

Technical data

Rated voltage & Rated current: see tables below

Compatible fuse links

See table below

Standards / Agency information

see table below



Size	Catalogue numbers		Rated voltage & rated current	Agency markings	Number of poles	Terminal rating	Rated breaking withstand capacity	Compatible Bussmann series fuse links
	With indicator	Without indicator						
CHM 10x38 and Midget	CHM1DIU	CHM1DU	IEC 690 V a.c./32A UL 600 V a.c./30 A;	IEC 60269-2 UR; CSA; CCC	1	IEC: 1 to 25mm ² 70°C PVC/Copper Cable Solid, Stranded, Fine Stranded, Spade Lug, Comb Bus Bar, Single and Dual	IEC 120 kA rms sym UL 200 kA rms sym CCC 100 kA rms sym	IEC: C10 UL: FNQ, KLM, FNM, KTK, BAF, FWA, PVM, AGU, BAN, FWC.
	CHM2DIU	CHM2DU			2			
	CHM3DIU	CHM3DU			3			
	CHM4DIU	CHM4DU			4			
	CHM1DNIU	CHM1DNU		1-pole + 1 neutral				
	CHM3DNIU	CHM3DNU		3-pole + 1 neutral				
	CHM1DI-48U	N/A	IEC 48V d.c./32A UL 48V d.c./30 A;	IEC 60269-2; UR; CSA; CCC	1		N/A	N/A
	N/A	CHM1DNXU	IEC 690 V a.c./32A	IEC 60269-2	1 neutral			
CHPV Photovoltaic	CHPV1IU	CHPV1U	IEC 1000 V d.c./32A UL 1000 V d.c./30 A;	IEC 60269-1 UR; CSA; CCC UL4248-18	1		33kA	Solar PV , PVM, PV-xxA10F
	CHPV2IU	CHPV2U			2			
CHCC Class CC	CHCC1DIU	CHCC1DU	UL 600 V a.c./30 A 600 V d.c./30 A	UL; CSA; CCC	1	Cable 75oC and 90oC Cu cable	200 kA rms sym	LP-CC, FNQ-R, KTK-R
	CHCC2DIU	CHCC2DU			2			
	CHCC3DIU	CHCC3DU			3			
	N/A	CHCC1DI-48U			1			