


## DG M H TT 275 (952 381)


- Prewired complete unit consisting of a base part and plug-in protection modules
- High discharge capacity due to heavy-duty zinc oxide varistors / spark gaps
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG M H TT 275



Dimension drawing DG M H TT 275

Modular surge arrester with an increased discharge capacity for TT and TN-S systems (3+1 configuration).

Type	DG M H TT 275
Part No.	952 381
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment ( $\leq 10$ m)	type 2 + type 3
Nominal voltage (a.c.) ( $U_N$ )	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [L-N] ( $U_C$ )	275 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [N-PE] ( $U_C$ )	255 V (50 / 60 Hz)
Nominal discharge current (8/20 $\mu$ s) [L-N] ( $I_n$ )	20 kA
Nominal discharge current (8/20 $\mu$ s) [N-PE] ( $I_n$ )	80 kA
Max. discharge current (8/20 $\mu$ s) [L-N] ( $I_{max}$ )	40 kA
Max. discharge current (8/20 $\mu$ s) [N-PE] ( $I_{max}$ )	120 kA
Voltage protection level [L-N]/[N-PE] ( $U_P$ )	$\leq 1.5 / \leq 1.5$ kV
Voltage protection level [L-N] / [N-PE] at 5 kA ( $U_P$ )	$\leq 1 / \leq 1.5$ kV
Follow current extinguishing capability [N-PE] ( $I_f$ )	100 A <sub>rms</sub>
Response time [L-N] ( $t_A$ )	$\leq 25$ ns
Response time [N-PE] ( $t_A$ )	$\leq 100$ ns
Max. mains-side overcurrent protection	125 A gG
Short-circuit withstand capability for max. mains-side overcurrent protection ( $I_{SCCR}$ )	50 kA <sub>rms</sub>
Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic	335 V / 5 sec. – withstand
Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic	440 V / 120 min. – safe failure
Temporary overvoltage (TOV) [N-PE] ( $U_T$ ) – Characteristic	1200 V / 200 ms – withstand
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm <sup>2</sup> solid / flexible
Cross-sectional area (max.)	35 mm <sup>2</sup> stranded / 25 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA
Lightning impulse current (10/350 $\mu$ s) [N-PE] ( $I_{imp}$ )	40 kA
Weight	405 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364318144
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.