


## DG M TNC CI 275 (952 304)


- Arrester backup fuse integrated in the protection module
- Prewired complete unit consisting of a base part and plug-in protection modules
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG M TNC CI 275



Dimension drawing DG M TNC CI 275

Modular surge arrester with integrated backup fuses for TN-C systems.

| Type   | DG M TNC CI 275<br>952 304                                |
|--|---|
| Part No.   |   |
| SPD according to EN 61643-11 / IEC 61643-11                | type 2 / class II   |
| Energy coordination with terminal equipment ( $\leq 10$ m) | type 2 + type 3   |
| Nominal a.c. voltage ( $U_N$ )                             | 230 / 400 V (50 / 60 Hz)                                  |
| Max. continuous operating voltage (a.c.) ( $U_c$ )         | 275 V (50 / 60 Hz)  |
| Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )         | 12.5 kA   |
| Max. discharge current (8/20 $\mu$ s) ( $I_{max}$ )        | 25 kA   |
| Voltage protection level ( $U_P$ )                         | $\leq 1.5$ kV   |
| Voltage protection level at 5 kA ( $U_P$ )                 | $\leq 1$ kV   |
| Response time ( $t_A$ )                                    | $\leq 25$ ns  |
| Max. mains-side overcurrent protection                     | not required  |
| Rated breaking capacity of the internal backup protection  | 25 kA   |
| Short-circuit withstand capability ( $I_{SCCR}$ )          | 25 kA <sub>rms</sub>                                      |
| Temporary overvoltage (TOV) ( $U_T$ ) – Characteristic     | 335 V / 5 sec. – withstand                                |
| Temporary overvoltage (TOV) ( $U_T$ ) – Characteristic     | 440 V / 120 min. – safe failure                           |
| Operating temperature range ( $T_U$ )                      | -40 °C ... +80 °C   |
| Operating state / fault indication                         | green / red   |
| Number of ports  | 1   |
| Cross-sectional area (min.)                                | 1.5 mm <sup>2</sup> solid / flexible                      |
| Cross-sectional area (max.)                                | 35 mm <sup>2</sup> stranded / 25 mm <sup>2</sup> flexible |
| For mounting on  | 35 mm DIN rails acc. to EN 60715                          |
| Enclosure material   | thermoplastic, red, UL 94 V-0                             |
| Place of installation                                      | indoor installation                                       |
| Degree of protection                                       | IP 20   |
| Capacity   | 3 module(s), DIN 43880                                    |
| Approvals  | KEMA, VDE   |
| Weight   | 376 g   |
| Customs tariff number (Comb. Nomenclature EU)              | 85363030  |
| GTIN   | 4013364128361   |
| PU   | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.