

BST-05-USA



Designation

Electrical Socket BST-05-USA /USA/Canada clip for 35 mm DIN rail, EN 60715

Configuration / Extent of delivery:

BST-05-USA electrical Socket for USA/Canada

Quickly connected

Available with or without fuse

Clip fixing

Illustration with fuse

Technical Date:

- Connection: 3 cage clamps for solid and stranded wire AWG 20-14 (0,5-2,5 mm²)

- Mounting: Clip for 35 mm DIN-rail, EN 60715

- Casing: plastic according to UL94 V-0, light grey, RAL 7035

- Dimensions: 3.6 x 2.4 x 1.9 (92 x 62 x48 mm)

- Weight: approx. 7 oz. (0,20 kg)

Fitting position: variableNominal current: 15,0 A

- Operating voltage max.: 125 V AC

- Operating/Storage temperature : -49 to + 158 °F

- Operating/Storage humidity: max. 90 % RH (non-condensing)

- Protection type: IP20

- Protection Class: I (grounded)

Approbationen:

CF.



The DIN rail mounted electrical socket can be quickly fitted and connected in enclosures allowing the use of auxiliary products such as hand lamps, measuring devices, soldering irons etc. The unit is available with and without fuse and in many world socket standards.

Stand: 07.13

Dimensions:

