# PLUS 2 Panel printer

### Main features

- 200 dpi high printing quality
- Same mechanics as PlusII (100% compatible)
- Paper width 58 mm
- Paper thickness 55-70gr/mq
- Roll dimension Ø 50mm
- Power supply 4-7,5Vdc
- 4MB internal flash memory for logos and font
- Interfaces: RS232/TTL (selectable with lever switch), miniUSB
- Barcodes: 1D,2D and QRCODE
- Font: European, International, Portoguese and Nordic, Chinese (GB18030) and Cyrillic
- Sensors: head temperature, paper presence, door open (opt.)
- Approved for UL, CE, FCC

# **CUST**<sup>©</sup>M<sup>°</sup>



#### **Exclusive features**

- RGB status LED
- FEED button
- ECO MODE



#### Linerless capability

With one printer model it's possible to print on "linerless" adhesive paper or on standard thermal paper, satisfying different needs and applications.

# Options

• Extended range module 8-42V

# Available versions

- RS232/TTL and miniUSB, 4-7,5 Vdc
- Mechanism version (without electronic board)

## Most common applications

- Garage equipments
- Medical equipments
- PC panel and control systems
- Weighing equipments: industrial, portable
- Fire detection systems
- Sterilisation equipments
- Taximeters
- Trucks tachograph
- Access control
- Measurement systems: durometer, electricity etc...