

Calmo M 2102 i5-7500T, 4GB, 120GB SSD, W10Pro

The reliable companion for demanding industrial applications



- integrated Fujitsu industrial mainboard
- fanless and robust housing
- · suitable for rough and dusty environments
- · Intel® processor technology
- · developed and manufactured in Germany







Reliable and fail-safe hardware in professional environments is indispensable. With its fanless, compact housing and the high-quality Fujitsu industrial mainboards it is the first choice for rough environments. If you are searching for a system that is prepared for 7x24 hour operation and almost completety closed, you will successfully stop searching now. Only choose between embedded CPUs for low power consumption or Desktop CPUs for high power output. First class industrial IT components - developed and manufactured in Germany.



fanless



Watchdog functionality



noiselessly



24-hour burn-in test



long-term availability



serial interface



Protected against dust in damaging quantity

Errors and changes excepted Illustration may differ from the actual product.









processor

installed operating

hard disk

marking

working memory max

graphic onBoard

PXE support

Wake on LAN (WOL)

audio

rear interfaces

expansion slots

RAID SATA3 onBoard

Intel® Core™ i5-7500T (4x 2.70 GHz up to 3.30 GHz with Intel® Turbo Boost Technology, HD 630, 6M Cache)

Windows 7/8 drivers are no longer provided for Intel® Kaby Lake processors

Windows® 10 Pro 64-bit

4 GB DDR4 PC2400 SO-DIMM

120 GB SSD 2.5" SATA3 with 6 GB/s

Powered by Fujitsu® - Made in Germany

D3433-S

2x SO-DIMM DDR4 PC2133, max. 32 GB (supports dual channel memory architecture)

Intel® HD Graphics, DirectX12 support (with appropriate CPU)

yes

yes

yes

Realtek ALC 671 5.1-Channel High Definition Audio

4x USB 3.0, 4x USB 2.0, 2x PS/2, 1x DVI-D, 2x DisplayPort, 2x LAN, Line-In, Line-Out, 1x serial

1x PCIe x16 3.0, 1x miniPCIe (half-size/full-size with mSATA), 1x PCIe M.2

2x USB 3.0, 2x USB 2.0, 1x USB 3.0 port, 1x serial, TPM, 6x SATA3 (6Gb/s), GPIO, LVDS, Backlight Inverter

0/1/5/10

24-hour continuous operation	yes
chassis	exone® fanless Calmo M
internal drive bays	2x 2,5"
fanless	yes
degree of protection	IP 50
color	silver
dimensions with feet (W x H x D)	260 x 93 x 237 mm
dimensions without feet (W x H x D)	260 x 87 x 237 mm
power supply	84 Watt, external input: 90-264V AC / 47-63Hz Output: 12V DC / 7A
24/7 suitable	yes
guarantee	2 years Bring-In
system check	24-hour burn-in test
slot bracket extension	1x serial (slot bracket with 9pin serial plug)