

SOLID PC 3828 13 G



Sample photo

Order symbol: PC 3828 13 G
Product nbr: 5330363
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074005564
EI. number:
 Finland: 3423717
 Electric No. Italy: 7401050
 Electric No. Sweden: 2539422

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

| Dimensions: | | | Accessories: | |
|-------------------------------------|----------------------|--------|---|-------------------------|
| Length | Width | Height | | |
| mm: | 378 | 278 | EKPXT | Mounting plate Pertinax |
| inch: | 14.9 | 10.9 | EKV 22 | DIN-35 Mounting rail |
| | | | EKV 32 | DIN-35 Mounting rail |
| | | | EKPZR | Extension frame |
| Materials: | | | Rating: | |
| Material: | Polycarbonate | | Ingress Protection (EN 60529): IP66/IP67 | |
| Base colour: | RAL 7035 -light grey | | Impact Resistance (EN 62262): IK08/IK09 | |
| Cover screws material: | Polyamide | | Electrical insulation: Totally insulated | |
| Cover colour: | RAL 7035 -light grey | | Halogen free (DIN/VDE 0472, Part 815): 1 | |
| Cover screws colour: | Grey | | UV resistance: UL 508 | |
| Gasket material: | Polyurethane | | Flammability Rating: UL 746C 5V | |
| | | | Glow Wire Test (IEC 695-2-1) °C: 960 | |
| | | | NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12 | |
| Temperatures: | | | Certificates: | |
| Temperature °C (short term): | -40 ... 120 °C | | SGS Fimko | |
| Temperature °C (continuous): | -40 ... 80 °C | | | |
| Temperature °F (short term): | -40 ... 250 °F | | | |
| Temperature °F (continuous): | -40 ... 175 °F | | | |
| Accessories: | | | | |
| EKPVT | Mounting plate | | | |

