

Vibrating Armature Pumps & Compressors

VACUUM								DIMENSIONS
Model	Motor		Flow l/min @ mbar				max. Vacuum	H x W x L
	Voltage	Type*	0	-100	-200	-400	mbar rel.	mm
106	230/50	VA						60 x 60 x 90
107	230/50	VA	1,2	0,6			-190	60 x 60 x 90
112.0	230/50	VA						81 x 78 x 113
112.1	230/50	VA						81 x 78 x 113
113.0	230/50	VA	4,2	2,0	1,2		-280	81 x 78 x 113
113.1	230/50	VA	3,2	2,5	1,6	0,4	-450	81 x 78 x 113
122.0	230/50	VA						83 x 70 x 128
122.1	230/50	VA						83 x 70 x 128
123.0	230/50	VA	4,2	2,0	1,5		-280	83 x 70 x 128
123.1	230/50	VA	3,3	2,5	1,5	0,3	-430	83 x 70 x 128
202.0	230/50	VA						91 x 70 x 140
202.1	230/50	VA						91 x 70 x 140
203.0	230/50	VA	4,6	2,5	1,2		-300	91 x 70 x 140
203.1	230/50	VA	5,5	4,0	2,3	0,6	-450	91 x 70 x 140
302.0	230/50	VA						97 x 78 x 165
302.1	230/50	VA						97 x 78 x 165
303.0	230/50	VA	5,5	3,5	2,2	0,5	-420	97 x 78 x 165
303.1	230/50	VA	6,8	5,0	3,6	2,0	-550	97 x 78 x 165
312	230/50	VA						84 x 65 x 162
362	230/50	VA						84 x 65 x 162
313	230/50	VA	6,2	3,3	0,7		-250	84 x 65 x 162
363	230/50	VA	8,5	4,4			-230	84 x 65 x 162
D300	230/50	VA	8,8	4,7	2,2		-310	120 x 35 x 180
Q500	230/50	VA	16,7	10,1	4,3		-280	120 x 35 x 180
Q800	230/50	VA	19,9	15,1	8,9		-380	120 x 35 x 180

* VA = Vibrating armature



106



310/360



310/360


WEIGHT		PRESSURE							
Weight	Model	Motor		Flow				max. Pressure	
		Voltage	Type*	l/min @ mbar				cont.	interm.
kg				0	100	200	400	mbar	
0,3	106	230/50	VA	0,9	0,6	0,2		200	270
0,3	107	230/50	VA						
0,8	112.0	230/50	VA	2,8	2,0	1,2		280	280
0,8	112.1	230/50	VA	5,0	2,6	2,0		340	340
0,8	113.0	230/50	VA						
0,8	113.1	230/50	VA						
1,1	122.0	230/50	VA	2,7	2,0	1,2		280	280
1,1	122.1	230/50	VA	5,0	2,8	1,9		340	340
1,1	123.0	230/50	VA						
1,1	123.1	230/50	VA						
1,6	202.0	230/50	VA	4,6	3,3	1,7		340	340
1,6	202.1	230/50	VA	4,8	3,8	2,1	0,3	450	450
1,6	203.0	230/50	VA						
1,6	203.1	230/50	VA						
2,2	302.0	230/50	VA	5,5	4,3	3,0	1,0	500	500
2,2	302.1	230/50	VA	8,5	6,5	5,2	3,0	700	700
2,2	303.0	230/50	VA						
2,2	303.1	230/50	VA						
0,9	312	230/50	VA	6,2	3,8	1,7		270	270
0,9	362	230/50	VA	8,5	4,6			200	200
0,9	313	230/50	VA						
0,9	363	230/50	VA						
0,9	D300	230/50	VA	7,5	5,0	3,0		300	300
0,9	Q500	230/50	VA	15,0	8,5	2,5		-	200
0,9	Q800	230/50	VA	18,0	14,0	7,5		-	400



Q 800



113



303