

Technical characteristics	Value
Protection index IP	30
Insulation class	isol.class II
Fixing mode	hollow wall
Quantity of rows in enclosure	3
Number of modules	36
Width of installed product	348 mm
Height of installed product	630 mm
Depth of installed product	94.5 mm
Colour	white
Enclosure material	plastic
Type of door closing	?
Number of doors	1
Number of keylock of the door	0
RAL colour number	9010
Material	plastic
Add. label text 1	3x12M
CE marking on label	1
Copper weight of the product	0.13 kg
Equipement system	2
European directive RoHs	voluntary compliance
European directive WEEE	not concerned
Free text for packaging label	Volta
GWT Glow wire test	850 °C
LabelText: Label Colour	LABEL_WHITE.JPG
Number of packaging labels per ref.	2
Packaging label design	IP30
Packaging label design (next for multi-line design)	Hollow wall mount. enclosure
Packaging label design (next 2 for multi-line design)	DIN VDE 0603 + DIN 43871
Packaging label design (next 3 for multi-line design)	QuickConnect
Pricing increase class for copper	Z
Protection code against mecanical chocs IK	07
Quantity of half modules of 17,7mm	72
Quantity of rails	3
Rating current	63 A
Symbol of isolation class for type plate	SCHUTZKLASSE_002I_D.JPG
Type label is active / inactive	1
Width in division units	12