


Cable junction boxes with UL/CSA approval (Nema 4X)




- without terminals
- with UL/CSA approval
- box walls without knockouts
- wall surface can be drilled individually for cable entry M 20/25/32, NPT 3/8", NPT 1/2", NPT 3/4" and 1"
- colour: grey, RAL 7032


wall thickness of the bottom part	2,8 mm
external brackets	2
Degree of protection:	IP 65 (Nema 4X)
Material:	PC-GFS (polycarbonate)
mounting width	141 mm
mounting height	99 mm
max. installation depth	64 mm
width	167 mm
height:	125 mm
depth	82 mm
Weight	0,417 kg
Approbation	UL/CSA: E207549

Drawings


Dimension drawing




Cable junction boxes with UL/CSA approval (Nema 4X)



Detail mass




box walls




Operating and ambient conditions





Application area	Suitable for outdoor installation (harsh environment and/or outdoor). To reduce the formation and accumulation of condensed water see technical information.
Resistant to occasional cleaning procedures (direct jet)	Resistant to occasional cleaning procedures (direct jet) with high-pressure cleaner without additives, water pressure: max. 100 bar, water temperature: max. 80° C, distance => 0,15 m, in accordance with the requirements IP 69K, enclosure and cable glands at least IP 65
Ambient temperature	Average value over 24 hours + 55 °C Maximum value + 70 °C Minimum value - 25 °C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60 695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position

Cable junction boxes with UL/CSA approval (Nema 4X)



KF 7100



Burning behaviour	Glow wire test IEC 60 695-2-11: 960 °C UL Subject 94: V-0 flame resistant self-extinguishing
Degree of protection against mechanical load	IK08 (5 Joule)
Toxic behaviour	halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 754-2

Note: For material properties see technical data.