


Product Sheet

Part Number: CKM 04



Family	inserts
Version	screw terminal connections
Series	CK
Product type	with male contacts
Execution	white colour coded
Model	male insert
Reference standard	EN 61984 (2001-11)
Contact type	silver plated
No. of poles	4 poles + ⊕
Voltage (V)	250V
Current (A)	10A (A.C. and D.C.)
Wire section	0,75mm ² - 2,5mm ²
Awg size	18 - 14
Quality mark	

The information and the dimensions contained are not binding and may be changed without prior notice.
The drawing's dimensions are in mm.

IP degree of protection IP20 degree of protection without enclosure, IP44 and IP66/67 with enclosure (EN 60529)

Fixing centre distance size "21.21"

Impulse withstand voltage 4kV

Pollution degree 3

Notes

CKM inserts:

- characteristics according to EN 61984:
(10A 250V 4kV 3)
(10A 230/400V 4kV 2)
- inserts for connectors with the following sections: 0.75 - 2.5 mm² - AWG 18 - 14
- can be mated with CKS inserts
- torsion couple recommended for conductor fastening screws and stripping length see section feature of inserts
- for maximum current load, see the insert load curve section
- inserts and enclosures for application with temperatures up to 180°C, available on request.

The information and the dimensions contained are not binding and may be changed without prior notice.
The drawing's dimensions are in mm.