

Internal mounting plate: L -55 mm H -55 mm

Useful surface (door): L -70 mm H -70 mm

Useful Depth: P -20 mm

Door opening: 145°

Order code	Model	Nr. Door	Ext. dim. mm			kg	m ³
			L	H	P		
013110550	EKO 20 30 15*	1	200	300	155	7,0	0,02
013110560	EKO 25 35 21	1	250	350	210	9,0	0,04
013110570	EKO 30 30 21*	1	300	300	210	9,0	0,04
013110580	EKO 30 38 21	1	300	380	210	10,0	0,04
013110590	EKO 30 45 21	1	300	450	210	11,5	0,05
013110600	EKO 35 40 21	1	350	400	210	11,5	0,05
013110620	EKO 38 38 21	1	380	380	210	11,0	0,05
013110630	EKO 38 60 21	1	380	600	210	12,5	0,08
013110640	EKO 40 35 21	1	400	350	210	11,5	0,05
013110660	EKO 45 45 21	1	450	450	210	12,5	0,07
013110610	EKO 45 45 25	1	450	450	250	15,0	0,08
013110670	EKO 45 45 30	1	450	450	300	18,0	0,10
013110650	EKO 40 50 25	1	400	500	250	12,5	0,08
013110680	EKO 45 60 25	1	450	600	250	19,5	0,11
013110690	EKO 45 60 30	1	450	600	300	22,5	0,12
013110700	EKO 45 60 40	1	450	600	400	28,5	0,16
013110710	EKO 50 50 21	1	500	500	210	13,5	0,09
013110720	EKO 50 50 30	1	500	500	300	19,0	0,12
013110730	EKO 50 70 25	1	500	700	250	26,0	0,14
013110750	EKO 60 45 25	1	600	450	250	19,5	0,11
013110760	EKO 60 60 21	1	600	600	210	25,0	0,12

Order code	Model	Nr. Door	Ext. dim. mm			kg	m ³
			L	H	P		
013110770	EKO 60 60 25	1	600	600	250	26,0	0,14
013110780	EKO 60 60 40	1	600	600	400	29,5	0,21
013110790	EKO 60 75 25	1	600	750	250	30,0	0,17
013110800	EKO 60 75 30	1	600	750	300	33,0	0,20
013110810	EKO 60 75 40	1	600	750	400	37,0	0,25
013110830	EKO 60 90 30	1	600	900	300	38,0	0,23
013110840	EKO 60 90 40	1	600	900	400	42,0	0,30
013110850	EKO 60 120 30**	1	600	1200	300	49,0	0,30
013110860	EKO 60 120 40**	1	600	1200	400	53,0	0,39
013110870	EKO 70 50 25	1	700	500	250	26,0	0,14
013110880	EKO 75 60 25	1	750	600	250	30,0	0,17
013110890	EKO 75 100 30	1	750	1000	300	49,5	0,31
013110900	EKO 76 76 30	1	760	760	300	46,0	0,25
013110910	EKO 80 100 30	1	800	1000	300	51,0	0,33
013110920	EKO 80 120 30**	1	800	1200	300	61,0	0,40
013110930	EKO 90 60 30	1	900	600	300	38,0	0,24
013110940	EKO 100 75 30	1	1000	750	300	49,5	0,32
013110950	EKO 100 100 30	1	1000	1000	300	63,5	0,41
013110960	EKO 100 120 30	1	1000	1200	300	64,0	0,49
013110970	EKO 120 60 30	2	1200	600	300	49,0	0,31
013110980	EKO 120 80 30	2	1200	800	300	61,0	0,40

* 1 central lock - ** 3 locks

All data can undergo changes without notice.



Protection window
P. 88



Rain canopy
P. 87






Ventilation kit IP55
P. 117



Standard operating

EKO with solid hinged door, internal mounting plate. Equipped with back threaded nuts with M6 screws.

Category of protection and certification	 IP66 IK10	EN 60 529/09.2000 EN 50 102/05.96
	 TYPE 4x 12, 1, 4 NEMA 4x 12, 1, 4	Standard 508 Standard 250
	 EN 62208 : 2003	89/392/EEC
Thickness	According to external dimensions 1,2 / 1,5 mm	
Material	AISI 304 Wnr. 1.4301 brushed fine scotch brite medium	
Internal mounting plate	2,5 mm FeZn	
on request	Manufacturing in AISI 316 Wnr. 1.4404	

AISI 304 watertight stainless steel enclosures, with solid door, can be fixed on machineries or walls. They are provided with back threaded nuts with M6 screws. Models starting from W=1200 mm are equipped with two overlapping doors L=600 mm, without central post.