



Technical data

Delta connection with discharge resistor - Protection type: IP00 – Frequency: 50 Hz

Nominal output in kvar at a nominal voltage of:					Type	Capacitance in μF -5 ... + 10 %	Dimensions in mm (D x H)	Weight in kg	Item no.
400 V	415 V	440 V	480 V	525 V					
2.4	2.6	2.9	3.5	4.17	JCP525/4.1-D	3 x 16.0	60 x 225	0.7	19.02.275
2.5	2.7	3.0	3.6	4.3	JCP480/3.6-D	3 x 16.6	60 x 150	0.5	19.02.205
4.8	5.2	5.8	7	8.33	JCP525/8.3-D	3 x 32.0	70 x 225	0.9	19.02.249
5	5.4	6	7.2	8.6	JCP480/7.2-D	3 x 33.2	60 x 225	0.8	19.02.210
5.8	6.3	7	8.33	10	JCS525/10.0-D	3 x 38.5	70 x 225	0.8	19.02.150
6.25	6.7	7.6	9.0	-	JCP440/7.6-D	3 x 41.7	60 x 225	0.7	19.02.211
7.2	7.8	8.7	10.5	12.5	JCS525/12.5-D	3 x 48.1	70 x 225	1.1	19.02.180
8.7	9.4	10.5	12.5	15	JCS525/15.0-D	3 x 57.7	70 x 265	1.2	19.02.103
7.5	8.1	9.1	10.8	-	JCP440/9.1-D	3 x 49.9	70 x 225	0.7	19.02.215
10	10.8	12.1	14.4	-	JCP440/12.1-D	3 x 66.3	70 x 225	1.1	19.02.217
10.8	11.6	13.1	15.5	-	JCS480/15.5-D	3 x 71.4	70 x 225	1.1	19.02.116
9.3	10	11.2	-	-	JCP400/9.3-D	3 x 61.4	70 x 225	1.1	19.02.219
10	10.8	12.1	-	-	JCP400/10.0-D	3 x 66.3	70 x 225	1.1	19.02.220
11.7	12.5	14.1	-	-	JCP400/11.7-D	3 x 77.3	70 x 225	1.1	19.02.221
12.5	13.4	15.1	-	-	JCS440/15.0-D	3 x 82.9	70 x 225	1.1	19.02.125
20	-	24.2	-	-	JCP400/20.0-D	3 x 132.6	85 x 285	2.4	19.02.228
23.3	25.1	28.2	-	-	JCS440/28.2-D	3 x 154.6	85 x 355	2.5	19.02.126
25	29.9	30.2	-	-	JCS440/30.0-D	3 x 164.4	85 x 355	2.6	19.02.127

Protective caps / connection adapter	Type		Item no.
Protective cap with cable entry Height +77 mm	SK60	For power capacitors with a diameter of 60 mm	19.02.620
Protective cap with cable entry Height +75 mm	SK70	For power capacitors with a diameter of 70 mm	19.02.621
Connection adapter for D 60 / 70 mm with spring type terminals 2 x 6 mm ²	ASS 1	Height = 28 mm	19.02.610
Connection adapter for D85 mm with spring type terminals 16 mm ²	ASS 2	Height = 30.5 mm	19.02.612