

LED Maschinenleuchte *LED machine luminaire*

TUBELED_40 Element AC



Anschlusswerte / connected load	220 – 240 V AC, 50 – 60 Hz
Lichtverteilung / light distribution	direkt / <i>direct</i>
Entblendung / glare-free	Diffusor, PMMA, gefrostet / <i>diffusor, PMMA, frosted</i>
Abstrahlwinkel / beam angle	100°
Lichtfarbe / light colour	5200 - 5700 K
Farbwiedergabe (Ra) / color rendering	Ra > 80
Schutzart / system of protection	IP54
Schutzklasse / class of protection	I
Betriebstemperatur / operating temperature	-30... +50 °C
Lebensdauer / lifetime	> 50.000 Betriebsstunden / <i>operating hours (L70/B10)</i>
Leuchtengehäuse / luminaire body	Aluminium, Endkappen Kunststoff <i>aluminium, endcaps made of plastics</i>
Netzanschluss / main supply	M12 S-kodiert / <i>M12 S coded</i>
Befestigung / fastening	Montage über Leuchtenhalter (optional) <i>installation using luminair holder (optional)</i>
Risikogruppe / risk group (DIN EN 62471)	freie Gruppe / <i>free group</i>

TUBELED_40 Element AC | 230V AC | 5200K-5700K

Art.-Nr. <i>item no.</i>	LED-Leuchte <i>LED luminaire</i>	Länge <i>length [A]</i>	Leistungsaufnahme <i>power consumption</i>	Lichtstrom <i>luminous flux</i>	Effizienz <i>efficiency</i>	Gewicht (netto) <i>weight (net)</i>
119110-03	TUBELED_40 Element AC	280 mm	~8,5 W	1030 lm	127 lm/W	340 g
119310-03	TUBELED_40 Element AC	540 mm	~17 W	2060 lm	127 lm/W	690 g
119510-03	TUBELED_40 Element AC	1040 mm	~34 W	5120 lm	127 lm/W	1290 g
119610-03	TUBELED_40 Element AC	1540 mm	~51 W	6180 lm	127 lm/W	1840 g

