

MC Technologies MC66 Terminal

MC66 Terminal - Made by MC Technologies

GSM/GPRS-Terminal for all basic M2M solutions

Technical Data:

- Dualband GSM 900/1800MHz (MC66-E)
Quadband GSM 850/900/1800/1900 MHz (MC66-W)
- GPRS multi-slot class 10 (MC66-W)
- GPRS multi-slot class 8 (MC66-E)
- TCP/IP stack access via AT commands
- Input voltage range: 8 ... 30 V
- Operation temperature: -30°C ... +85°C
- Extended temperature range: -40°C ... -30°C und +85°C ... +90°C
- Dimensions: 65 x 74 x 33 mm
- Weight: approx. 110 g
- GPRS:** DL: max. 85.6 kbps / UL: max. 42.8 kbps (MC66-W), UL: max. 21.4 kbps (MC66-E),
Mobile station class B, PBCCH support, Coding schemes CS 1-4
- Data:** CSD up to 14.4 kbps, V.110, Non-transparent mode, USSD support
- SMS:** Point-to-Point MO and MT, SMS cell broadcast, Text- and PDU-mode
- Fax:** Group 3, Class 1
- Interfaces:** Power supply, SIM card reader, FME antenna connector (male), RS232 (V.24/V.28 on sub-D)



MC Technologies MC66-E/MC66-W Terminal and accessoires

Article Description	Article No.
MC66-E Terminal - Made by MC Technologies -	MC1213652-Terminal
MC66-W Terminal - Made by MC Technologies -	MC1213653-Terminal
Power supply incl. connecting cable / Western plug, EU plug	MC1213114-45-EU
Power supply incl. connecting cable / Western plug, UK plug	MC1213114-45-UK
Power supply incl. connecting cable / Western plug, US plug	MC1213114-45-US
Power adapter Western Plug / open end, approx. 1,5m	MC1213115
12-24V Car adapter 1,5 m cable, Western plug, for battery pack	MC1213116
Data cable 1,8m, 9 pin male - 9 pin female	MC1213226
Battery pack 100% cutoff incl. cable 0,2 m Western plug (RJ10) / Western plug (RJ12)	MC1213150
Mounting Kit incl. 2 fixing bolts	Mounting Kit TC/MC



MC1213114-45-EU/-UK/-US



MC1213115



MC1213116



MC1213226



Mounting Kit TC/MC