

**Indicator light, Flat, Cable (black) with non-terminated end, 4 pole, 1 m,  
Lens white, LED white, 24 V AC/DC**

**Part no. C22-L-W-24-P62  
185142**

Product name	Eaton Moeller® series C22 Indicator light
Part no.	C22-L-W-24-P62
EAN	4015081806249
Product Length/Depth	1061 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.046 kilogram
Certifications	IEC/EN 60947-5-1 CE CSA UL VDE 0660
Product Tradename	C22
Product Type	Indicator light
Product Sub Type	None
Bezel color	Other
Bezel material	Plastic
Design	Flat Cable end open
Electric connection type	Other
Fitted with:	Front ring Light source
Lens color	White
Light color	White
Cable length	1 m
Cable material	PUR
Connection to SmartWire-DT	No
Connection type	Cable (black) with non-terminated end, 4 pole
Degree of protection	IP Other NEMA Other
Mounting position	As required
Opening diameter	22.5 mm
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	800 V AC
Shock resistance	30 g, Mechanical, Shock duration 11 ms
Tightening torque	2 Nm, Threaded ring
Type	Indicator lights
Voltage type	AC/DC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Rated conditional short-circuit current (Iq)	1 kA
Rated insulation voltage (Ui)	30 V
Rated operational voltage	24 V AC/DC (LED)

Rated operational voltage (Ue) - min		24 V
Rated operational voltage (Ue) - max		24 V
Short-circuit protection rating		Max. 4 A gG/gL, Fuse, Contacts
Actuator diameter		4.7 mm

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Indicator light complete (EC000272)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Indicator light complete (ecl@ss10.0.1-27-37-12-23 [AKF041014])		
Number of indicator lights		1
Colour lens		White
Type of lamp socket		LED
With light source		Yes
Rated operating voltage Ue	V	24 - 24
Voltage type		AC/DC
Type of electric connection		Other
Construction type lens		Round
Type of lens		Flat
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
With front ring		Yes
Material front ring		Plastic
Colour front ring		Other
Degree of protection (IP)		Other
Degree of protection (NEMA)		Other