

**Indicator light, Flat, Cable (black) with non-terminated end, 4 pole, 1 m,
Lens yellow, LED white, 24 V AC/DC**

**Part no. C22-L-Y-24-P62
185143**

Product name	Eaton Moeller® series C22 Indicator light
Part no.	C22-L-Y-24-P62
EAN	4015081806256
Product Length/Depth	1061 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.046 kilogram
Certifications	VDE 0660 CSA IEC/EN 60947-5-1 UL CE
Product Tradename	C22
Product Type	Indicator light
Product Sub Type	None
Bezel color	Other
Bezel material	Plastic
Design	Cable end open Flat
Electric connection type	Other
Fitted with:	Front ring Light source
Lens color	Yellow
Light color	White
Cable length	1 m
Cable material	PUR
Connection to SmartWire-DT	No
Connection type	Cable (black) with non-terminated end, 4 pole
Degree of protection	IP Other NEMA Other
Mounting position	As required
Opening diameter	22.5 mm
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	800 V AC
Shock resistance	30 g, Mechanical, Shock duration 11 ms
Tightening torque	2 Nm, Threaded ring
Type	Indicator lights
Voltage type	AC/DC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Rated conditional short-circuit current (Iq)	1 kA
Rated insulation voltage (Ui)	30 V
Rated operational voltage	24 V AC/DC (LED)

Rated operational voltage (Ue) - min		24 V
Rated operational voltage (Ue) - max		24 V
Short-circuit protection rating		Max. 4 A gG/gL, Fuse, Contacts
Actuator diameter		4.7 mm

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Indicator light complete (EC000272)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Indicator light complete (ecl@ss10.0.1-27-37-12-23 [AKF041014])		
Number of indicator lights		1
Colour lens		Yellow
Type of lamp socket		LED
With light source		Yes
Rated operating voltage Ue	V	24 - 24
Voltage type		AC/DC
Type of electric connection		Other
Construction type lens		Round
Type of lens		Flat
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
With front ring		Yes
Material front ring		Plastic
Colour front ring		Other
Degree of protection (IP)		Other
Degree of protection (NEMA)		Other