



**Circuit-breaker, 3p, 630A**

**Part no.** NZMN3-VE630  
**259133**  
**EL Number** 4358791  
**(Norway)**

|                      |  |
|----------------------|--|
| Product name         | Eaton Moeller series NZM - Molded Case Circuit Breaker |
| Part no.             | NZMN3-VE630  |
| EAN                  | 4015082591335  |
| Product Length/Depth | 166 millimetre   |
| Product height       | 275 millimetre   |
| Product width        | 140 millimetre   |
| Product weight       | 7.083 kilogram   |
| Compliances          | RoHS conform   |
| Certifications       | IEC/EN 60947<br>IEC                                    |
| Product Tradename    | NZM  |
| Product Type         | Molded Case Circuit Breaker                            |
| Product Sub Type     | None   |
| Globally Marketable  | Yes  |

|                            |  |
|----------------------------|--|
| Application                | Use in unearthed supply systems at 690 V   |
| Type                       | Circuit breaker  |
| Circuit breaker frame type | NZM3   |
| Number of poles            | Three-pole   |
| Amperage Rating            | 630 A  |
| Release system             | Electronic release   |
| Features                   | Motor drive optional<br>Protection unit  |
| Special features           | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> R.m.s. value measurement and "thermal memory" Adjustable time delay setting to overcome current peaks $t_{tr}$ at 6 x I <sub>r</sub> also infinity (without overload releases) Adjustable delay time $t_{sd}$ i't constant function: switchable Rated current = rated uninterrupted current: 630 A Terminal capacity hint: Up to 240 mm <sup>2</sup> can be connected depending on the cable manufacturer. |

|   |               |
|---|---------------|
| Voltage rating  | 690 V - 690 V |
| Rated insulation voltage (U <sub>i</sub> )  | V             |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts                   | 6000 V        |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts                        | 8000 V        |
| Rated short-time withstand current (t = 0.3 s)  | 3.3 kA        |
| Rated short-time withstand current (t = 1 s)  | 3.3 kA        |
| Instantaneous current setting (I <sub>i</sub> ) - min                                       | 1260 A        |
| Instantaneous current setting (I <sub>i</sub> ) - max                                       | 5040 A        |
| Overload current setting (I <sub>r</sub> ) - min  | 315 A         |
| Overload current setting (I <sub>r</sub> ) - max  | 630 A         |
| Short delay current setting (I <sub>sd</sub> ) - min  | 472 A         |
| Short delay current setting (I <sub>sd</sub> ) - max  | 4410 A        |
| Short-circuit release delayed setting - min   | 472.5 A       |
| Short-circuit release delayed setting - max   | 4410 A        |
| Short-circuit release non-delayed setting - min   | 1260 A        |
| Short-circuit release non-delayed setting - max   | 5040 A        |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz     | 85 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz | 50 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz     | 35 kA         |

|   |  |  |
|---|--|--|
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz |  | 13 kA  |
| Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz |  | 5 kA   |
| Rated short-circuit making capacity Icm at 240 V, 50/60 Hz                  |  | 187 kA   |
| Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz              |  | 105 kA   |
| Rated short-circuit making capacity Icm at 440 V, 50/60 Hz                  |  | 74 kA  |
| Rated short-circuit making capacity Icm at 525 V, 50/60 Hz                  |  | 53 kA  |
| Rated short-circuit making capacity Icm at 690 V, 50/60 Hz                  |  | 40 kA  |
| Short-circuit total breaktime   |  | < 10 ms  |
| Electrical connection type of main circuit                                  |  | Screw connection   |
| Isolation   |  | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts)   |
| Number of operations per hour - max   |  | 60   |
| Handle type   |  | Rocker lever   |
| Utilization category  |  | A (IEC/EN 60947-2)   |
| Overvoltage category  |  | III  |
| Pollution degree  |  | 3  |
| Lifespan, electrical  |  | 2000 operations at 400 V AC-3<br>5000 operations at 415 V AC-1<br>2000 operations at 690 V AC-3<br>2000 operations at 415 V AC-3<br>3000 operations at 690 V AC-1<br>5000 operations at 400 V AC-1 |
| Direction of incoming supply  |  | As required  |

|   |  |   |
|---|--|---|
| Mounting Method   |  | Fixed<br>Built-in device fixed built-in technique   |
| Degree of protection                                    |  | IP20<br>IP20 (basic degree of protection, in the operating controls area)   |
| Degree of protection (IP), front side                   |  | IP40 (with insulating surround)<br>IP66 (with door coupling rotary handle)  |
| Degree of protection (terminations)                     |  | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)  |
| Protection against direct contact                       |  | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110   |
| Shock resistance  |  | 20 g (half-sinusoidal shock 20 ms)  |
| Number of auxiliary contacts (change-over contacts)     |  | 0   |
| Number of auxiliary contacts (normally closed contacts) |  | 0   |
| Number of auxiliary contacts (normally open contacts)   |  | 0   |
| Position of connection for main current circuit         |  | Front side  |
| Climatic proofing                                       |  | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78  |
| Special features  |  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn) R.m.s. value measurement and "thermal memory" Adjustable time delay setting to overcome current peaks $I_{tr}$ at $6 \times I_r$ also infinity (without overload releases) Adjustable delay time $t_{sd}$ i't constant function: switchable Rated current = rated uninterrupted current: 630 A Terminal capacity hint: Up to 240 mm <sup>2</sup> can be connected depending on the cable manufacturer. |
| Lifespan, mechanical                                    |  | 15000 operations  |

|   |  |  |
|---|--|--|
| Standard terminals                                    |  | Screw terminal   |
| Optional terminals                                    |  | Box terminal. Connection on rear. Tunnel terminal  |
| Terminal capacity (control cable)                     |  | 0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)<br>0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)   |
| Terminal capacity (aluminum solid conductor/cable)    |  | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>16 mm <sup>2</sup> (1x) at tunnel terminal<br>16 mm <sup>2</sup> (1x) direct at switch rear-side connection  |
| Terminal capacity (aluminum stranded conductor/cable) |  | 25 mm <sup>2</sup> - 120 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 120 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>50 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x) at 2-hole tunnel terminal<br>50 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) at 2-hole tunnel terminal<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at tunnel terminal |
| Terminal capacity (copper busbar)                     |  | Min. 20 mm x 5 mm direct at switch rear-side connection<br>Max. 30 mm x 10 mm + 30 mm x 5 mm direct at switch rear-side connection<br>M10 at rear-side screw connection<br>Max. 10 mm x 50 mm (2x) at rear-side width extension  |
| Terminal capacity (copper solid conductor/cable)      |  | 16 mm <sup>2</sup> (1x) at tunnel terminal<br>16 mm <sup>2</sup> (1x) direct at switch rear-side connection  |

|   |  |  |
|---|--|--|
|   |  | 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>300 mm <sup>2</sup> (2x) at rear-side width extension<br>16 mm <sup>2</sup> (2x) at box terminal  |
| Terminal capacity (copper stranded conductor/cable) |  | 50 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) at 2-hole tunnel terminal<br>16 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at 1-hole tunnel terminal<br>35 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x) at box terminal<br>25 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 120 mm <sup>2</sup> (2x) at box terminal<br>25 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) direct at switch rear-side connection |
| Terminal capacity (copper strip)                    |  | Max. 8 segments of 24 mm x 1 mm (2x) at box terminal<br>10 segments of 50 mm x 1 mm (2x) at rear-side width extension<br>Min. 6 segments of 16 mm x 0.8 mm at box terminal<br>Max. 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm at rear-side connection (punched)<br>Max. 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm<br>Min. 6 segments of 16 mm x 0.8 mm at rear-side connection (punched)  |

|   |  |          |
|---|--|----------|
| Rated operational current for specified heat dissipation (In) |  | 630 A    |
| Equipment heat dissipation, current-dependent                 |  | 119.07 W |
| Ambient operating temperature - min                           |  | -25 °C   |
| Ambient operating temperature - max                           |  | 70 °C    |
| Ambient storage temperature - min                             |  | 40 °C    |
| Ambient storage temperature - max                             |  | 70 °C    |

|  |  |  |
|--|--|--|
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

|           |  |  |
|-----------|--|--|
| Functions |  | Systems, cable, selectivity and generator protection |
|-----------|--|--|

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

|   |    |               |
|---|----|---------------|
| Rated permanent current I <sub>u</sub>                                | A  | 630           |
| Rated voltage   | V  | 690 - 690     |
| Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, 50 Hz | kA | 50            |
| Overload release current setting                                      | A  | 315 - 630     |
| Adjustment range short-term delayed short-circuit release             | A  | 472 - 4,410   |
| Adjustment range undelayed short-circuit release                      | A  | 1,260 - 5,040 |
| Integrated earth fault protection                                     |    | No            |

|   |  |  |  |
|---|--|--|--|
| Type of electrical connection of main circuit           |  |  | Screw connection                         |
| Device construction                                     |  |  | Built-in device fixed built-in technique |
| Suitable for DIN rail (top hat rail) mounting           |  |  | No                                       |
| DIN rail (top hat rail) mounting optional               |  |  | No                                       |
| Number of auxiliary contacts as normally closed contact |  |  | 0  |
| Number of auxiliary contacts as normally open contact   |  |  | 0  |
| Number of auxiliary contacts as change-over contact     |  |  | 0  |
| With switched-off indicator                             |  |  | No                                       |
| With integrated under voltage release                   |  |  | No                                       |
| Number of poles   |  |  | 3  |
| Position of connection for main current circuit         |  |  | Front side                               |
| Type of control element                                 |  |  | Rocker lever                             |
| Complete device with protection unit                    |  |  | Yes                                      |
| Motor drive integrated                                  |  |  | No                                       |
| Motor drive optional                                    |  |  | Yes                                      |
| Degree of protection (IP)                               |  |  | IP20                                     |