

USB cable - NBC-USB2.0-UAM/3,0-PVC/UAM



1333140

<https://www.phoenixcontact.com/de/produkte/1333140>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



USB cable, type: USB-A, degree of protection: IP20, cable length: 3 m, number of positions: 9, cable outlet: straight, USB 2.0

Your advantages

- Data transmission up to 480 Mbps
- Reliable data transmission thanks to 100 % testing

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 1333140 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales Key | D1 - Steckverbinder |
| Product Key | ABNDBA |
| GTIN | 4063151630812 |
| Weight per Piece (including packing) | 113,8 g |
| Weight per Piece (excluding packing) | 113,8 g |
| Customs tariff number | 85444290 |
| Country of origin | CN |

1333140

<https://www.phoenixcontact.com/de/produkte/1333140>

Technical Data

Product properties

| | |
|---------------------|-------------------------|
| Type | USB-A |
| Product type | Data cable preassembled |
| Number of positions | 9 |
| Connection profile | USB-A |
| Cable outlet | straight |

Insulation characteristics

| | |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

Electrical properties

| | |
|--------------------|---------------|
| Contact resistance | < 40 Ω |
|--------------------|---------------|

Mechanical properties

Mechanical data

| | |
|-------------------------------------|-----------|
| Insertion/withdrawal cycles | > 1500 |
| Insertion force per signal contact | < 35.00 N |
| Extraction force per signal contact | < 10 N |

Material specifications

| | |
|---------------------------|-------|
| Color of the housing part | black |
|---------------------------|-------|

Dimensions

| | |
|--------|---------|
| Width | 15.8 mm |
| Height | 8 mm |
| Length | 45 mm |

Connector

Connection 1

| | |
|-----------------------|---------------|
| Insulation resistance | 10 M Ω |
| Degree of protection | IP20 |

Cable / line

| | |
|--------------|--------|
| Cable length | 3.00 m |
|--------------|--------|

Ambient conditions

| | |
|---|------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -25 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

USB cable - NBC-USB2.0-UAM/3,0-PVC/UAM



1333140

<https://www.phoenixcontact.com/de/produkte/1333140>

Classifications

ECLASS

ECLASS-11.0

27440390

ETIM

ETIM 8.0

EC001121

UNSPSC

UNSPSC 21.0

39121400

USB cable - NBC-USB2.0-UAM/3,0-PVC/UAM



1333140

<https://www.phoenixcontact.com/de/produkte/1333140>

Environmental Product Compliance

China RoHS

Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de