

RAD-ISM-2400-ANT-PAN- 8-0

Order No.: 2867610



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867610>

Panel antenna, degree of protection IP55, 8 dBi gain, linear vertical, SMA (female), impedance 50 ohms, apex angle h/v 75°/70°

Commercial data

GTIN (EAN)	4017918938994
sales group	H179
Pack	1 pcs.
Customs tariff	85177019
Weight/Piece	0.1512 KG
Catalog page information	Page 535 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
01/08/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Frequency range	2.3 GHz ... 2.8 GHz
Horizontal beamwidth	75 °
Vertical beamwidth	70 °
Impedance	50 Ω
Gain	8 dBi

Wind load	15 N (at 160 km/h)
Type of connection	SMA (female)
Degree of protection	IP55
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Width	80 mm
Height	100 mm
Length	20 mm

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;