

## Plug-in bridge - FBS 5-8 - 3030310

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in bridge, Pitch: 8.2 mm, Length: 3 mm, Width: 39.3 mm, Number of positions: 5, Color: red

### Why buy this product

- ✔ The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

### Key Commercial Data

|                                      |                      |
|--------------------------------------|----------------------|
| Packing unit                         | 10 STK               |
| Minimum order quantity               | 10 STK               |
| GTIN                                 |                      |
| GTIN                                 | 4017918188443        |
| Weight per Piece (excluding packing) | 9.250 g              |
| Weight per piece (including packing) | 9.760 g              |
| Custom tariff number                 | 85389099             |
| Country of origin                    | Germany              |
| Sales Key                            | A1 - Terminal Strips |

### Technical data

#### Technical data

|  |   |
|--|---|
| Color                                  | red   |
| Material                               | Copper  |
| Number of positions                    | 5   |
| Pitch                                  | 8.2 mm  |
| Maximum load current                   | 41 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
| Flammability rating according to UL 94 | V0  |

### Standards and Regulations

# Plug-in bridge - FBS 5-8 - 3030310

## Technical data

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141140 |
| eCl@ss 5.1 | 27141140 |
| eCl@ss 6.0 | 27141140 |
| eCl@ss 7.0 | 27141140 |
| eCl@ss 8.0 | 27141140 |
| eCl@ss 9.0 | 27141140 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000489 |
| ETIM 3.0 | EC000489 |
| ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 |
| ETIM 6.0 | EC000489 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211829 |
| UNSPSC 7.0901 | 39121426 |
| UNSPSC 11     | 39121426 |
| UNSPSC 12.01  | 39121426 |
| UNSPSC 13.2   | 39121426 |

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

## Plug-in bridge - FBS 5-8 - 3030310

### Approvals

#### Approval details

|     |            |               |
|-----|------------|---------------|
| EAC | <b>EAC</b> | EAC-Zulassung |
|-----|------------|---------------|

### Accessories

#### Accessories

#### Cutting tools

Front cutter - CUTFOX-FBS - 1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges