

Reducing bridge - RB ST 6-1,5/S - 3213250

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing bridge, Pitch: 8 mm, Length: 29.9 mm, Width: 12.9 mm, Number of positions: 2, Color: red

The figure shows a version of the article



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	
GTIN	4046356572019
Weight per Piece (excluding packing)	3.220 g
Weight per piece (including packing)	3.220 g
Custom tariff number	85389099
Country of origin	Poland
Sales Key	A1 - Terminal Strips

Technical data

Technical data

Color	red
Material	Copper
Number of positions	2
Pitch	8 mm
Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Reducing bridge - RB ST 6-1,5/S - 3213250

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 4.0	EC002018
ETIM 5.0	EC000489
ETIM 6.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426