

# RIF-2-BPT/4X21 - Relay base



2900934

<https://www.phoenixcontact.com/de/produkte/2900934>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Relay base RIF-2..., for industrial relay with 2 or 4 changeover contacts, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5



## Commercial data

Item number	2900934
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	G1 - Relais
Product key	CK6523
Catalog page	Page 298 (C-5-2019)
GTIN	4046356733175
Weight per piece (including packing)	68,7 g
Weight per piece (excluding packing)	62,825 g
Customs tariff number	85366990
Country of origin	CN

# RIF-2-BPT/4X21 - Relay base



2900934

<https://www.phoenixcontact.com/de/produkte/2900934>

## Technical data

### Product properties

Product type	Relay socket
Product family	RIFLINE complete

### Data management status

Article revision	06
------------------	----

### Electrical properties

Nominal voltage $U_N$	250 V AC/DC
Nominal current $I_N$	max. 12 A (Depends on application/assembly)
Protective circuit	depending on the selected input/suppressor modules

### Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrule with plastic sleeve)
	0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve, two conductors on double terminal block)
Conductor cross section AWG	26 ... 16 (solid)
	26 ... 16 (flexible)

### Dimensions

#### Drill hole

Diameter	3.2 mm
Width	31 mm
Height	96 mm
Depth Retaining bracket	75 mm (with retaining bracket)

### Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V2 (Housing)

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (Depends on application/assembly)
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Approvals

#### Corrosive gas test

# RIF-2-BPT/4X21 - Relay base



2900934

<https://www.phoenixcontact.com/de/produkte/2900934>

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

# RIF-2-BPT/4X21 - Relay base



2900934


<https://www.phoenixcontact.com/de/produkte/2900934>

## Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/de/produkte/2900934>

 **CSA**  
Approval ID: 76787

 **UL Recognized**  
Approval ID: FILE E 113228

 **EAC**  
Approval ID: RU D-DE.B\*00573/18

 **DNV GL**  
Approval ID: TAA000018V

 **DNV GL**  
Approval ID: TAA000018V

# RIF-2-BPT/4X21 - Relay base



2900934

<https://www.phoenixcontact.com/de/produkte/2900934>

## Classifications

### ECLASS

ECLASS-11.0	27371603
ECLASS-12.0	27371603
ECLASS-13.0	27371603

### ETIM

ETIM 9.0	EC001456
----------	----------

### UNSPSC

UNSPSC 21.0	39122300
-------------	----------

# RIF-2-BPT/4X21 - Relay base



2900934

<https://www.phoenixcontact.com/de/produkte/2900934>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## Mandatory accessories

### REL-IR2/LDP- 12DC/2X21 - Single relay

2903659

<https://www.phoenixcontact.com/de/produkte/2903659>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 12 V DC

---

### REL-IR2/LDP- 24DC/2X21 - Single relay

2903660

<https://www.phoenixcontact.com/de/produkte/2903660>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 24 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR2/LDP- 48DC/2X21 - Single relay

2903661

<https://www.phoenixcontact.com/de/produkte/2903661>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 48 V DC

---

## REL-IR2/LDP- 60DC/2X21 - Single relay

2903662

<https://www.phoenixcontact.com/de/produkte/2903662>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 60 V DC



# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR2/LDP-110DC/2X21 - Single relay

2903663

<https://www.phoenixcontact.com/de/produkte/2903663>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 110 V DC

---

## REL-IR2/LDP-125DC/2X21 - Single relay

2903664

<https://www.phoenixcontact.com/de/produkte/2903664>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 125 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR2/LDP-220DC/2X21 - Single relay

2903665

<https://www.phoenixcontact.com/de/produkte/2903665>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 220 V DC

---

## REL-IR2/L- 24AC/2X21 - Single relay

2903666

<https://www.phoenixcontact.com/de/produkte/2903666>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, mechanical switching position indicator, input voltage: 24 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR2/L-120AC/2X21 - Single relay

2903667

<https://www.phoenixcontact.com/de/produkte/2903667>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, mechanical switching position indicator, input voltage: 120 V AC

---

## REL-IR2/L-230AC/2X21 - Single relay

2903668

<https://www.phoenixcontact.com/de/produkte/2903668>



Plug-in industrial relay with power contacts, 2 changeover contacts, test button, status LED, mechanical switching position indicator, input voltage: 230 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP- 12DC/4X21 - Single relay

2903676

<https://www.phoenixcontact.com/de/produkte/2903676>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 12 V DC

---

## REL-IR4/LDP- 24DC/4X21 - Single relay

2903677

<https://www.phoenixcontact.com/de/produkte/2903677>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, input voltage: 24 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP- 48DC/4X21 - Single relay

2903678

<https://www.phoenixcontact.com/de/produkte/2903678>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 48 V DC

---

## REL-IR4/LDP- 60DC/4X21 - Single relay

2903679

<https://www.phoenixcontact.com/de/produkte/2903679>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 60 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP-110DC/4X21 - Single relay

2903680

<https://www.phoenixcontact.com/de/produkte/2903680>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 110 V DC

---

## REL-IR4/LDP-125DC/4X21 - Single relay

2903681

<https://www.phoenixcontact.com/de/produkte/2903681>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 125 V DC

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



### REL-IR4/L- 24AC/4X21 - Single relay

2903686

<https://www.phoenixcontact.com/de/produkte/2903686>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switching position indicator, coil voltage: 24 V AC

---

### REL-IR4/L-120AC/4X21 - Single relay

2903687

<https://www.phoenixcontact.com/de/produkte/2903687>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switching position indicator, coil voltage: 120 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/L-230AC/4X21 - Single relay

2903688

<https://www.phoenixcontact.com/de/produkte/2903688>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switching position indicator, input voltage: 230 V AC

---

## REL-IR4/LDP- 12DC/4X21AU - Single relay

2903669

<https://www.phoenixcontact.com/de/produkte/2903669>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 12 V DC



# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP- 24DC/4X21AU - Single relay

2903670

<https://www.phoenixcontact.com/de/produkte/2903670>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 24 V DC

---

## REL-IR4/LDP- 48DC/4X21AU - Single relay

2903671

<https://www.phoenixcontact.com/de/produkte/2903671>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 48 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP- 60DC/4X21AU - Single relay

2903672

<https://www.phoenixcontact.com/de/produkte/2903672>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 60 V DC

---

## REL-IR4/LDP-110DC/4X21AU - Single relay

2903673

<https://www.phoenixcontact.com/de/produkte/2903673>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 110 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/LDP-220DC/4X21AU - Single relay

2903675

<https://www.phoenixcontact.com/de/produkte/2903675>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 220 V DC

---

## REL-IR4/LDP-220DC/4X21 - Single relay

2903682

<https://www.phoenixcontact.com/de/produkte/2903682>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 220 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/L- 24AC/4X21AU - Single relay

2903683

<https://www.phoenixcontact.com/de/produkte/2903683>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, mechanical switching position indicator, coil voltage: 24 V AC

---

## REL-IR4/L-120AC/4X21AU - Single relay

2903684

<https://www.phoenixcontact.com/de/produkte/2903684>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, mechanical switching position indicator, coil voltage: 120 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/L-230AC/4X21AU - Single relay

2903685

<https://www.phoenixcontact.com/de/produkte/2903685>



Plug-in industrial relay with power contacts and additional hard gold plating, 4 changeover contacts, test button, status LED, mechanical switching position indicator, coil voltage: 230 V AC

---

## REL-IR2/24DC/2X21 - Single relay

2907051

<https://www.phoenixcontact.com/de/produkte/2907051>



Plug-in industrial relay with power contacts, 2 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 24 V DC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR2/100AC/2X21 - Single relay

2907052

<https://www.phoenixcontact.com/de/produkte/2907052>



Plug-in industrial relay with power contacts, 2 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 100 V AC

---

## REL-IR2/200AC/2X21 - Single relay

2907053

<https://www.phoenixcontact.com/de/produkte/2907053>



Plug-in industrial relay with power contacts, 2 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 200 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/24DC/4X21 - Single relay

2907054

<https://www.phoenixcontact.com/de/produkte/2907054>



Plug-in industrial relay with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 24 V DC

---

## REL-IR4/100AC/4X21 - Single relay

2907055

<https://www.phoenixcontact.com/de/produkte/2907055>



Plug-in industrial relay with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 100 V AC

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## REL-IR4/200AC/4X21 - Single relay

2907056

<https://www.phoenixcontact.com/de/produkte/2907056>



Plug-in industrial relay with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity: bipolar, input voltage: 200 V AC

---

## Accessories

### FBS 2-6 - Plug-in bridge

3030336

<https://www.phoenixcontact.com/de/produkte/3030336>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red



# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## FBS 2-6 BU - Plug-in bridge

3036932

<https://www.phoenixcontact.com/de/produkte/3036932>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

---

## FBS 2-6 GY - Plug-in bridge

3032237

<https://www.phoenixcontact.com/de/produkte/3032237>



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: gray

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



### STP 5-2 - Marker carriers

0800967

<https://www.phoenixcontact.com/de/produkte/0800967>



Marker carriers, snaps into STTB 2,5, STTB 4, PTTB 2,5, and PTTB 4 double-level spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray, unlabeled, mounting type: plug in, lettering field size: 5 x 10.5 mm

---

### RIF-RH-2 - Retaining bracket

2900954

<https://www.phoenixcontact.com/de/produkte/2900954>



Relay retaining bracket, with ejector function and holder for marking material, suitable for RIF-2 relay base, for industrial relay

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-RHS-2 - Retaining bracket

2908043

<https://www.phoenixcontact.com/de/produkte/2908043>



Reinforced relay retaining bracket, with eject function and holder for marking material, suitable for RIF-2 relay base, for industrial relays

---

## RIF-RHM-2 - Relay retaining bracket

2905984

<https://www.phoenixcontact.com/de/produkte/2905984>



Relay retaining bracket, wire model, suitable for RIF-2 relay base

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/de/produkte/0201744>



Test plug, with solder connection up to 1 mm<sup>2</sup> conductor cross section, number of positions: 1, color: gray

---

## RIF-LDP-12-24 DC - Plug-in module

2900939

<https://www.phoenixcontact.com/de/produkte/2900939>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 12 V DC ... 24 V DC  $\pm 30\%$

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-LDP-48-60 DC - Plug-in module

2900940

<https://www.phoenixcontact.com/de/produkte/2900940>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 48 V DC ... 60 V DC  $\pm 20$  %

---

## RIF-LDP-110 DC - Plug-in module

2900941

<https://www.phoenixcontact.com/de/produkte/2900941>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 110 V DC  $\pm 20$  %

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-LV-12-24 UC - Plug-in module

2900942

<https://www.phoenixcontact.com/de/produkte/2900942>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 12 V AC ... 24 V AC / DC  $\pm$ 20 %

---

## RIF-LV-48-60 UC - Plug-in module

2900943

<https://www.phoenixcontact.com/de/produkte/2900943>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 48 V AC ... 60 V AC / DC  $\pm$ 20 %

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-LV-120-230 AC/110 DC - Plug-in module

2900944

<https://www.phoenixcontact.com/de/produkte/2900944>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 120 V AC... 230 V AC / 110 V DC  $\pm 20$  %

---

## RIF-V-12-24 UC - Plug-in module

2900945

<https://www.phoenixcontact.com/de/produkte/2900945>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 12 V AC ... 24 V AC / DC  $\pm 20$  %

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-V-48-60 UC - Plug-in module

2900947

<https://www.phoenixcontact.com/de/produkte/2900947>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 48 V AC ... 60 V AC / DC  $\pm$ 20 %

---

## RIF-V-120-230 UC - Plug-in module

2900948

<https://www.phoenixcontact.com/de/produkte/2900948>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor, input voltage: 120 V AC ... 230 V AC / DC  $\pm$ 20 %



## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-RC-12-24 UC - Plug-in module

2900949

<https://www.phoenixcontact.com/de/produkte/2900949>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with RC element, input voltage: 12 V AC ... 24 V AC / DC  $\pm 20$  %

---

## RIF-RC-48-60 UC - Plug-in module

2900950

<https://www.phoenixcontact.com/de/produkte/2900950>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with RC element, input voltage: 48 V AC ... 60 V AC / DC  $\pm 20$  %

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-RC-120-230 UC - Plug-in module

2900951

<https://www.phoenixcontact.com/de/produkte/2900951>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with RC element, input voltage: 120 V AC ... 230 V AC / DC  $\pm 20\%$

---

## RIF-T3-24UC - Timer module

2902647

<https://www.phoenixcontact.com/de/produkte/2902647>



Plug-in module for extending a relay module to create a timer relay, 3 time functions, 4 time ranges, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, input voltage: 12 V DC ... 24 V DC

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## RIF-BR-12-230 AC - Plug-in module

2907060

<https://www.phoenixcontact.com/de/produkte/2907060>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with bridge rectifier, input voltage: 12 V AC ... 230 V AC

---

## RIF-LDM-12-24 DC - Plug-in module

2907057

<https://www.phoenixcontact.com/de/produkte/2907057>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with freewheeling diode and yellow LED, input voltage: 12 V DC ... 24 V DC  $\pm 20\%$ , polarity A1-, A2+

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/de/produkte/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/de/produkte/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/de/produkte/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/de/produkte/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/de/produkte/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/de/produkte/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/de/produkte/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/de/produkte/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/de/produkte/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



---

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/de/produkte/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver



# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/de/produkte/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/de/produkte/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/de/produkte/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/de/produkte/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/de/produkte/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/de/produkte/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

## RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/de/produkte/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/de/produkte/1206573>

DIN rail end piece, for DIN rail NS 35/15



# RIF-2-BPT/4X21 - Relay base

2900934

<https://www.phoenixcontact.com/de/produkte/2900934>



## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/de/produkte/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

[info@phoenixcontact.de](mailto:info@phoenixcontact.de)