

## Touch panel - TP 07T - 2913085

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Touch panel with 17.8 cm (7") graphics-capable TFT display, 65,535 colors, 800 x 480 pixels, 1 x Ethernet, 2 x USB, and integrated runtime of the Visu+ visualization software.

### Why buy this product

- Short startup time
- Easy installation, low installation depth, and compact design
- Display available in sizes from 8.9 cm (3.8") to 38.1 cm (15")
- Visu+ RT and AX OPC server integrated as standard in all devices

### Key commercial data

Packing unit	1 pc
GTIN	 4 046356 299831
Weight per Piece (excluding packing)	1276.0 g
Weight per piece (including packing)	1598.0 g
Custom tariff number	84714100
Country of origin	Germany
Sales Key	P1 - HMIs + Industry PC

### Technical data

#### Note:

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

External dimension, width	203 mm
External dimension, height	147 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	195 mm
Installation dimension, height	139 mm

#### Display

Display	17.8 cm/7" TFT
---------	----------------

# Touch panel - TP 07T - 2913085

## Technical data

### Display

Resolution	800 x 480 Pixel (WVGA)
Backlighting	LED
Display backlight MTBF	> 50000 h
Touch screen	Resistive industrial touch screen
Colors	65,536 colors

### Computer data

Processor	RISC ARM9™ CPU; 200 MHz
RAM	64 MB SDRAM
Mass storage	32 MByte flash memory
Interfaces	2x USB Host 2.0
Network	1 x Ethernet (10/100 Mbps), RJ45
Operating systems	Windows CE 5.0

### General

Mounting type	Installation in front plate
---------------	-----------------------------

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

## Classifications

### eCl@ss

eCl@ss 4.0	27330202
eCl@ss 4.1	27330202
eCl@ss 5.0	27242215
eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301
eCl@ss 8.0	27242301

### ETIM

ETIM 2.0	EC001426
ETIM 3.0	EC001426
ETIM 4.0	EC001426
ETIM 5.0	EC001414

# Touch panel - TP 07T - 2913085

## Classifications

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43211903
UNSPSC 13.2	43201404

## Approvals

### Approvals

#### Approvals

UL Listed / cUL Listed / LR / GL / BV / DNV / ABS / GL-SW / UL Listed / cUL Listed / LR / GL / BV / DNV / ABS / GL-SW / GL / cULus Listed

#### Ex Approvals

#### Approvals submitted

### Approval details

UL Listed

cUL Listed

LR

GL

BV

DNV

ABS

GL-SW

# Touch panel - TP 07T - 2913085

## Approvals

UL Listed

cUL Listed

LR

GL

BV

DNV

ABS

GL-SW

GL

cULus Listed

## Accessories

### Accessories

#### Battery module

Battery - HMI BATTERY - 2701383

CMOS battery



---

## Mounting material

## Touch panel - TP 07T - 2913085

### Accessories

#### Mounting kit - HMI WALL MOUNTING KIT - 2701380

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



---

#### Mounting material - HMI WALL BOX - 2701381



Flush-type box made of galvanized sheet steel for panel mounting.

---

#### Mounting kit - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

---

#### Mounting kit - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

---

#### Mounting kit - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

---

### Operating stylus

## Touch panel - TP 07T - 2913085

### Accessories

Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

---

### Protective foil

Protective foil - 7" DISPLAY PROTECTIVE FOIL - 2701374



Protective film set comprising 10 pieces of film for a 7" display. Including a squeegee to apply film and instructions.

---

### Storage medium

USB memory stick - 2 GB USB STICK - 2701382



USB memory stick, 2 GB.

---