

Bus system cable - VS-OE-OE-93B/... - 1417362

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



CAT5e, PROFINET cable, shielded, star quad, AWG 22 stranded (7-wire), RAL 6018 (yellow-green), variable length, by the meter



Key commercial data

| | |
|----------------------|---------------------------|
| Packing unit | 1 pc |
| Custom tariff number | 85444995 |
| Country of origin | Germany |
| Sales Key | C1 - Sensor-Acuator Cable |

Technical data

Dimensions

| | |
|-----------------|------------------------------|
| Length of cable | Free entry (0.5 ... 400.0 m) |
|-----------------|------------------------------|

General data

| | |
|----------------------|--------------------------------|
| Number of positions | 4 |
| Signal type/category | PROFINET CAT5 (IEC 11801:2002) |
| | PROFINET CAT5e (TIA 568B:2001) |

Cable

| | |
|------------------------------------|--------------------------------|
| Cable type | PROFINET |
| Cable type (abbreviation) | 93B |
| UL AWM style | 21694 |
| Signal type/category | PROFINET CAT5 (IEC 11801:2002) |
| | PROFINET CAT5e (TIA 568B:2001) |
| Cable structure | 1x4xAWG22/7; SF/TQ |
| Conductor cross section | 4x 0.34 mm ² |
| AWG signal line | 22 |
| Conductor structure signal line | 7x 0.25 mm |
| Core diameter including insulation | approx. 1.5 mm |
| Wire colors | White, yellow, blue, orange |
| Overall twist | Star quad |

Bus system cable - VS-OE-OE-93B/... - 1417362

Technical data

Cable

| | |
|---|--|
| Shielding | Aluminum-coated foil, tinned copper braided shield |
| Optical shield covering | 85 % |
| External sheath, color | Green RAL 6018 |
| Outer sheath thickness | approx. 0.9 mm |
| External cable diameter D | 6.5 mm ± 0.2 mm |
| Minimum bending radius, fixed installation | 3 x D |
| Minimum bending radius, flexible installation | 7 x D |
| Torsion force | ± 180 °/m (30,000 torsion cycles) |
| Cable weight | 67 kg/km |
| Outer sheath, material | PVC |
| Material, inner sheath | PVC |
| Material conductor insulation | PE |
| Conductor material | Tin-plated Cu litz wires |
| Insulation resistance | ≥ 500 MΩ*km |
| Conductor resistance | ≤ 120 Ω/km |
| Working capacitance | 52 pF |
| Wave impedance | 100 Ω ± 15 Ω (At 100 MHz) |
| Signal runtime | 5.3 ns/m |
| Coupling resistance | ≤ 20.00 mΩ/m |
| Nominal voltage, cable | 600 V |
| Test voltage Core/Core | 2000 V (50 Hz, 1 min.) |
| Test voltage Core/Shield | 2000 V (50 Hz, 1 min.) |
| Flame resistance | According to UL 1685 (CSA FT 4) |
| Resistance to oil | Resistant to oil to a limited extent |
| Other resistance | UV resistant According to UL 1581, Section 1200 |
| Ambient temperature (operation) | -40 °C ... 70 °C (cable, fixed installation) |
| | -40 °C ... 70 °C (cable, flexible installation) |
| Ambient temperature (installation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -50 °C ... 70 °C |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27060307 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27449001 |

Bus system cable - VS-OE-OE-93B/... - 1417362

Classifications

ETIM


| | |
|----------|----------|
| ETIM 3.0 | EC000830 |
| ETIM 4.0 | EC002698 |
| ETIM 5.0 | EC000830 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121616 |
| UNSPSC 7.0901 | 26121616 |
| UNSPSC 11 | 26121604 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 26121616 |

Drawings

Cable cross section



PROFINET [93B]