

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2249.605

Date : Jun 18, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2249.605

created: 18.06.2018 on www.rittal.com/com-en



Product description

Design:	with mounting plate and mounting angles, static installation
Description:	Wall-mounted enclosure with optimum accessibility due to hinged part.
Material:	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Wall section with solid gland plate, top and bottom and mounting plate (supplied loose). Hinged part with 25 mm pitch pattern of holes in the front and rear frame, and two 482.6 mm (19") mounting angles, front, static installation Designer glazed door 1 double-kit key no. 5 Mini-comfort handle Security lock 3524 E
Basic material:	Sheet steel

Product features

Dimensions:	Width: 600 mm
--------------------	---------------

Height: 478 mm
Units: 9 U
Depth: 373 mm

Depth hinged part:	216 mm
Installation depth:	320 mm
Clearances:	Clearance width: 502 mm Clearance height: 415 mm
Mounting plate:	Width: 485 mm Height: 432 mm
Wall section:	Depth: 135 mm
Load capacity:	Hinged part, static (max.): 450 N
Packs of:	1 pc(s).
Weight/pack:	30 kg
EAN:	4028177324329
Customs tariff number:	94032080
ETIM 6.0:	EC002500
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	EL Wall-mounted enclosures, 3-part, 9 U, WHD: 600x478x373 mm, Protection category: IP 55, Designer glazed door
Approvals	
Approvals:	Germanischer Lloyd Lloyds Register of Shipping UL + C-UL
Certificates:	EAC Protection category

