




**MINI GC 9M-M**



**SPECIFICATION:**

1. VOLTAGE RATING: 300V AC(rms).
2. CURRENT RATING: 5 AMP CONTINUOUS
3. DIELECTRIC STRENGTH 1000VAC
4. CONTACT RESISTANCE: 10 m Ohm min
5. INSULATION RESISTANCE: 5000 M Ohm min
6. DURABILITY: 30 CYCLES FOR GOLD FLASH  
150 CYCLES FOR 15u" GOLD PLATED
7. CORROSION RESISTANCE: MEET M-STD-202F METHOD  
101 CONITION BSALT WATER  
SPRAY OR GOLD PLATED OVER 15u"  
AVERAGE 150 GRAM  
EXTRACTION FORCE: 1KG MIN
- 8.MATING FORCE INSERTION FORCE: 0Z-16 OZ

<b>PART NO. 0018</b>		Revision:	
APPROVED			
CHECKED	<b>JOAN</b>		
DRAWING	<b>CAT</b>		
ITEM NO.		ITEM NO.	
		<b>EB410</b>	
Cable Length		Tolerances:	
Unless Other Spec.		0 ~±0.2M	
		0.2~1.0M ±±0.2M	
		1.1 ~1.5M ±±0.25M	
		1.5~2.1M ±±0.5M	
		2.1M ±±0.4M	