

Product Specification



Product	CAT.5eSFTP 26AWG PATCH CORD-5	NO.	
K5455/K5457/K5458//K5459/K5460		Date	2003.3.20

Configuration

1 . Sketch	Unit (mm)					
	(1)	Connector	RJ45 Shielded Connector with 3μ-50μ Gold Plate			
	(2)	Plug-Body	PVC Molded With Strain Relief(Full-Length & with a Cap)			
	(3)	Cable	CAT5E SFTP26AWG standed×4pairs Cable			
2 . Pinout (100% tested)	B: For 568B to 568B					
3 . Packing	Unit mm		(L) Length	L < 10ft L < 3m	10ft < L < 30ft 3m < L < 10m	30ft < L 10m < L
			(A) Cable Width	110~130	130~150	150~180
			(B×C) PE bag size	150×175	180×190	220×260

Electric Characters

Impedance	Nom. 100 Ohm±20%										
Frequency MHz	1	4	8	10	16	20	25	31.25	62.5	100	155
NEXT (100% tested) dB	62.3	53.3	48.8	47.3	44.3	42.3	41.3	39.9	35.4	32.3	29.5
Attenuation dB/100m	2.4	4.9	6.9	7.8	9.9	11.1	12.5	14.1	20.4	26.4	33.7
Roturn loss dB	17	18.8	19.7	20	20	20	19.3	18.6	16.5	15.1	14
Acr dB	62.3	53.3	48.8	47.3	44.3	42.3	41.3	39.9	35.4	32.3	29.5