

# LS07-K-B-LED



Operating voltage:	220-240V 50/60Hz, 3 W
- motion sensor (operating time approx. 5 to 8 min.)	
- on/off switch	
- 2 m mains cable 2x0,75 mm <sup>3</sup> (orange)	
- electronic ballast to reduce interference when switching on and off, for extension of durability, faster switching and energy-saving effect with automatic shutdown in case of defect illuminant	
Lamp type:	3,5 W LED
Service life:	approx. 20.000 to 50.000 h
Colour of light:	cool white
Connections:	towards the sides
Fixing material:	special mirror tape
Fixing position:	for switch cabinets as from 300 mm width (ideal for wall cabinets)
Recommended fuse:	6A
Operating temperature :	-10°C to +40°C, (+14°F to +104°F) max. 90% RH (non-condensing)
Storage temperature:	-25°C to +60°C, (-13°F to +140°F)
Protection type/class:	IP 20, 2
Material:	PC or PA6
Color:	RAL 7035
<b>Approbation:</b>	<b>CE, EMV geprüft, entspricht RoHS</b>
<b>INDIVIDUAL PACKAGING</b>	
Customs tariff number:	85 39 31 90
Country of origin:	Germany

### Optional:

- for assembly in metal cabinets you receive the lamps with magnetic foil (pull-off approx. 3,5kg)

Article	Order-No.	Capacity	Dim. (L/W/H)	Description	Weight
LS07-K-B-LED	102245	3 W	146x85x43mm	without magnetic foil	0,4kg
LS07-K-B-LED-M20	102672	3 W	146x85x45mm	with magnetic foil	0,4kg