Rittal – The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1016.000

Date : Jan 16, 2020



ENCLOSURES

POWER DISTRIBUTION 📎 CLIMATE CONTROL

>> IT INFRASTRUCTURE >>> SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1016.000

created: 16.01.2020 on www.rittal.com/com-en



Product description	1
Material:	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel Stainless steel 1.4301 (AISI 304)
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 μm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Type rating to UL 508A:	Туре ЗХ/4Х
IK Code:	IK08
Supply includes:	Enclosure with door(s), opening angle 130° Mounting plate Lock: 3 mm double-bit
Basic material:	Stainless steel 1.4301 (AISI 304)
Product features	
Dimensions:	Width: 800mm Height: 1000mm Depth: 300mm

1

Mounting plate:	Width: 745 mm Height: 975 mm
Number of doors:	1
Number of cam locks:	2
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	52.9 kg
EAN:	4028177815025
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
e Cl@ss 8.0/8.1:	27180101
e Cl@ss 6.0/6.1:	27180101
Product description:	AX Compact enclosure, WHD: 800x1000x300 mm, stainless steel 1.4301, with mounting plate, single-door, with two cam locks