Rittal - The System.

Faster - better - everywhere.

AX Basic enclosure AX, stainless steel – AX 1019.000

Date: Dec 11, 2019



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1019.000

created: 11.12.2019 on www.rittal.com/com-en



_			
Prod	luct	desc	ription

Material: Enclosure: Stainless steel

Door: Stainless steel, all-round foamed-in PU seal

Mounting plate: Sheet steel

Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel

Stainless steel 1.4301 (AISI 304)

Surface finish: Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 55

Protection category NEMA:

NEMA 12

Type rating to UL

508A:

Type 1, 12

IK Code:

IK08

Supply includes:

Enclosure with door(s), opening angle 130°

Mounting plate

Lock: 3 mm double-bit

Basic material:

Stainless steel 1.4301 (AISI 304)

Product features

Dimensions: Width: 1000 mm

Height: 1200 mm Depth: 300 mm

© Rittal 2019

1

Mounting plate:	Width: 945 mm		
	Height: 1175 mm		
Number of doors:	2		
3-point lock system:	yes		
Lock version:	3-point lock system		
Number of locks:	1		
Lock insert:	3 mm double-bit		
Packs of:	1 pc(s).		
Weight/pack:	76 kg		
EAN:	4028177815056		
Customs tariff number:	94032080		
ETIM 7.0:	EC000261		
ETIM 6.0:	EC000261		
eCl@ss 8.0/8.1:	27180101		
eCl@ss 6.0/6.1:	27180101		
Product description:	AX Compact enclosure, WHD: 1000x1200x300 mm, stainless steel 1.4301, with mounting plate, two-door, with 3-point lock system		

© Rittal 2019