Rittal - The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, sheet steel – AX 1261.000

Date: Jan 29, 2020



Compact enclosure AX Basic enclosure AX, sheet steel – AX 1261.000

created: 29.01.2020 on www.rittal.com/com-en



Product description	
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Type rating to UL 508A:	Type 3R/4
Supply includes:	Enclosure with door(s) Gland plate(s) in enclosure base Mounting plate Perforated door strip Lock: 3 mm double-bit
Basic material:	Sheet steel
Product features	
Dimensions:	Width: 600 mm Height: 1200 mm

© Rittal 2020

Depth: 400 mm

Material thickness: Enclosure: 1.5 mm

Door: 2 mm

Mounting plate: 2.5 mm

Mounting plate: Width: 545 mm

Height: 1175 mm

Number of doors: 1

Door hinged on the right, may be swapped to the left:

yes

3-point lock system: yes

Lock insert: 3 mm double-bit

Gland plate, size: 7

Gland plate, qty.: 1

Packs of: 1 pc(s).

Weight/pack: 56 kg

EAN: 4028177813120

Customs tariff number:

94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

e Cl@ss 8.0/8.1: 27180101

eCl@ss 6.0/6.1: 27180101

Product description: AX Compact enclosure, WHD: 600x1200x400 mm, sheet steel, with mounting plate,

single-door, with 3-point lock system

Approvals

Approvals: UL + C-UL

Declarations: Declaration of conformity

© Rittal 2020 2