Rittal - The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1304.000

Date: Jan 29, 2020



Compact enclosure AX Basic enclosure AX, stainless steel – AX 1304.000

created: 29.01.2020 on www.rittal.com/com-en



Material: Enclosure: Stainless steel

Door: Stainless steel, all-round foamed-in PU seal

Mounting plate: Sheet steel

Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel

Stainless steel 1.4404 (AISI 316L)

Surface finish: Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 μm

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 66

Protection category NEMA:

NEMA 4X

Type rating to UL

508A:

Type 3X/4X

IK Code:

IK08

Supply includes:

Enclosure with door(s), opening angle 130°

Mounting plate

Lock: 3 mm double-bit

Basic material:

Stainless steel 1.4404 (AISI 316L)

Product features

Dimensions: Width: 600 mm

Height: 600 mm Depth: 210 mm

© Rittal 2020

1

Mounting plate:	Width: 550 mm Height: 575 mm
Number of doors:	1
Number of cam locks:	2
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	23.5 kg
EAN:	4028177815094
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX Compact enclosure, WHD: 600x600x210 mm, stainless steel 1.4404, with mounting plate, single-door, with two cam locks

© Rittal 2020 2