

# Rittal – The System.

Faster – better – everywhere.

## Plastic enclosures AX without viewing window – AX 1434.000

Date : Dec 16, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Plastic enclosures AX without viewing window – AX 1434.000

created: 16.12.2020 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Design:** without viewing window

**Applications:** Ambient temperature range: -35 °C...+80 °C  
The specified temperatures may be limited by the installed equipment

**Material:** Enclosure and door: Fibreglass-reinforced unsaturated polyester  
Door: All-round foamed-in PU seal  
Mounting plate: Sheet steel  
Fire protection corresponding to UL 94-V0

**Surface finish:** Enclosure and door: Dyed plastic with no after-treatment  
Mounting plate: Zinc-plated

**Colour:** Similar to RAL 7035

**Protection category  
IP to IEC 60 529:** IP 66

**Protection category  
NEMA:** NEMA 4X

**Type rating to UL  
508A:** Type 4X

**IK Code:** IK09

**Protection class:** II (at 1000 V AC)

**Supply includes:** Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock  
Door hinged on the right, may be swapped to the left  
Mounting plate

Twin seal on the top and bottom edges of the door as integral rain protection strip

|                               |   |
|-------------------------------|---|
| <b>Note:</b>                  | Interior installation screws are required to secure components inside the enclosure<br>Components such as punched sections with mounting flanges may be attached on a 25 mm pitch pattern using the universal bracket |
| <b>Basic material:</b>        | Plastic   |
| <b>Product features</b>       |   |
| <b>Dimensions:</b>            | Width: 300 mm<br>Height: 400 mm<br>Depth: 200 mm  |
| <b>Material thickness:</b>    | Mounting plate: 2 mm  |
| <b>Mounting plate:</b>        | Width: 205 mm<br>Height: 325 mm   |
| <b>Number of cam locks:</b>   | 2   |
| <b>Packs of:</b>              | 1 pc(s).  |
| <b>Weight/pack:</b>           | 6.64 kg   |
| <b>EAN:</b>                   | 4028177006409   |
| <b>Customs tariff number:</b> | 94037000  |
| <b>ETIM 7.0:</b>              | EC000261  |
| <b>ETIM 6.0:</b>              | EC000261  |
| <b>eCl@ss 8.0/8.1:</b>        | 27180101  |
| <b>eCl@ss 6.0/6.1:</b>        | 27180101  |
| <b>Product description:</b>   | AX compact enclosure, plastic, WHD: 300x400x200 mm  |
| <b>Approvals</b>              |   |
| <b>Approvals:</b>             | UL + C-UL   |
| <b>Declarations:</b>          | Declaration of conformity   |